

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **100-134 SOLVENT G**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 100-134

Synonym SOLVENT G

Chemical Name Not applicable.

Chemical Family Solvent. (Solvent.)

Chemical Formula Not applicable.

Material Uses Coatings: Solvent.

Product Identification Number (PIN) 1268 Petroleum Distillates, N.O.S.

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	<u>Exposure Limits</u>	
			LC ₅₀ /LD ₅₀	TLV/PEL
Heavy aromatic naphtha.	64742-94-5	100	ORAL (LD50): Acute: 3000 mg/kg [Rat]. DERMAL (LD50): Acute: 3001 mg/kg [Rabbit].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not applicable.

Boiling Point The lowest known value is 177.2°C (351°F) (Solvent naphtha (petroleum), heavy arom.).

Melting Point May start to solidify at -73°C (-99.4°F) based on data for: Solvent naphtha (petroleum), heavy arom..

Critical Temperature Not available.

Specific Gravity The only known value is 0.88 (Water = 1) (Solvent naphtha (petroleum), heavy arom.).

Vapor Pressure The highest known value is 0.009 kPa (0.07 mmHg) (at 20°C) (Solvent naphtha (petroleum), heavy arom.).

Vapor Density The highest known value is 4.8 (Air = 1) (Solvent naphtha (petroleum), heavy arom.).

Volatility Not available.

Odor Threshold Not available.

Water/Oil Dist. Coeff. The product is much more soluble in octanol.

Continued on Next Page

Ionicity (in Water)	Not available.
Dispersion Properties	Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in n-octanol. Soluble in diethyl ether. Partially soluble in methanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Combustible.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Special Remarks on Fire Hazards	Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back. (Solvent naphtha (petroleum), heavy arom.)
Flash Points	Closed cup: 66°C (150.8°F). (Tagliabue.)
Flammable Limits	The greatest known range is LOWER: 0.6% UPPER: 7% (Solvent naphtha (petroleum), heavy arom.)
Auto-Ignition Temperature	The lowest known value is 510°C (950°F) (Solvent naphtha (petroleum), heavy arom.).
Products of Combustion	Not available.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Highly explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents, acids, alkalis. Slightly reactive to reactive with reducing agents, organic materials.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3000 mg/kg (Rat) (Calculated value for the mixture). Acute dermal toxicity (LD50): 3001 mg/kg (Rabbit) (Calculated value for the mixture).
Effects of Acute Exposure	Very hazardous in case of eye contact (irritant), of inhalation. Hazardous in case of skin contact (irritant), of ingestion. Non-sensitizer for skin. Inflammation of the eye is characterized by redness, watering, and itching.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (Solvent naphtha (petroleum), heavy arom.)
Exposure Limits	Not available.

Continued on Next Page

Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.	
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.	
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk.	
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, alkalis.	
Storage	Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	
TDG Classification	3	
PIN	1268 Petroleum Distillates, PG: III N.O.S.	
Special Provisions for Transport		
Federal and State Regulations	No products were found.	
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	WHMIS (Canada)	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-2B: Material causing other toxic effects (TOXIC).
	HCS (U.S.A.)	Class: Irritating substance. Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).
Hazardous Material Information System (U.S.A.)	Health Hazard	2
	Fire Hazard	2
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	2
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Continued on Next Page

Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by C.M. Kelly on 8/26/2002. Verified by C.M. Kelly. Printed 10/1/2002.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.