

100-137 EEP

## 1. Product and company identification

**Code** : 100-137  
**Common name** : 100-137 EEP  
**Synonym** : EKTAPRO EEP  
**Material uses** : Coatings: Solvent for varnishes and lacquers.  
**Manufacturer** : Chemcraft International, Inc.  
155 Rose Glen Road North  
Port Hope, Ontario, Canada L1A 3Z3  
Ph:905-885-6388 Fax:905-885-7587  
**In case of emergency** : 1-613-996-6666  
**Validation date** : 2/1/2006.  
**Print date** : 2/10/2006.  
**Responsible name** : S.Bice

## 2. Hazards identification

**Physical state** : Liquid. (Clear liquid.)  
**Odor** : Ester-like.  
**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
**Emergency overview** : Caution!  
COMBUSTIBLE LIQUID AND VAPOR.  
VAPOR MAY CAUSE FIRE.  
Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation.  
**Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.  
**Potential acute health effects**  
**Eyes** : No known significant effects or critical hazards.  
**Skin** : Practically non-toxic in contact with skin.  
**Inhalation** : No known significant effects or critical hazards.  
**Ingestion** : Practically non-toxic if swallowed.  
**Potential chronic health effects** : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [100-137 EEP].  
**MUTAGENIC EFFECTS:** Not available.  
**TERATOGENIC EFFECTS:** Not available.

See toxicological information (section 11)

## 3. Composition/information on ingredients

<u>Name</u>	<u>CASnumber</u>	<u>%</u>
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	70 - 100

## 4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if symptoms occur. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms occur. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

## 5 . Fire-fighting measures

- Flammability of the product** : Combustible.
- Products of combustion** : These products are carbon oxides (CO, CO<sub>2</sub>).
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire Hazards in Presence of Various Substances** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
- Explosion Hazards in Presence of Various Substances** : Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.

## 6 . Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment. Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 6 . Accidental release measures

- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

## 7 . Handling and storage

- Handling** : Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

## 8 . Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Personal protection



- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9 . Physical and chemical properties

- Physical state** : Liquid. (Clear liquid.)
- Flash point** : Closed cup: 61°C (141.8°F). (Setaflash.)
- Auto-ignition temperature** : 377°C (710.6°F)
- Flammable limits** : Lower: 1.05%
- Color** : Colorless. (Light.)
- Odor** : Ester-like.
- Boiling/condensation point** : 165°C (329°F)

## 9 . Physical and chemical properties

<b>Melting/freezing point</b>	: -100°C (-148°F)
<b>Relative density</b>	: 0.95 (Water = 1)
<b>Vapor pressure</b>	: 0.1 kPa (0.9 mm Hg) (at 20°C)
<b>Vapor density</b>	: 5.03 (Air = 1)
<b>Volatility</b>	: 100% (v/v), 100% (w/w)
<b>Evaporation rate</b>	: 0.12 compared with Butyl acetate.
<b>VOC</b>	: 100 (%)
<b>Viscosity</b>	: Dynamic: 1.2 cP
<b>Dispersibility properties</b>	: See solubility in water.
<b>Solubility</b>	: Partially soluble in cold water, hot water.

## 10 . Stability and reactivity

<b>Stability and reactivity</b>	: The product is stable.
<b>Incompatibility with various substances</b>	: Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous polymerization</b>	: Will not occur.
<b>Conditions of reactivity</b>	: Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.

## 11 . Toxicological information

### Toxicity data

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
EKTAPRO EEP	LD50	5001 mg/kg	Oral	Rat
	LD50	4301 mg/kg	Oral	Rat
	LD50	10000 mg/kg	Dermal	Rabbit
Propanoic acid, 3-ethoxy-, ethyl ester	LD50	5001 mg/kg	Oral	Rat
	LD50	4301 mg/kg	Oral	Rat
	LD50	10000 mg/kg	Dermal	Rabbit
	LC50	>1000 ppm (6 hour/hours)	Inhalation	Rat

**Chronic effects on humans** : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [100-137 EEP].

**Other toxic effects on humans** : Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion.  
Slightly hazardous in case of inhalation.  
Non-sensitizer to skin.

### Specific effects

**Carcinogenic effects** : No known significant effects or critical hazards.

**Mutagenic effects** : No known significant effects or critical hazards.

**Teratogenicity / Reproductive toxicity** : No known significant effects or critical hazards.

### Sensitization

**Ingestion** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Eyes** : No known significant effects or critical hazards.

**Skin** : No known significant effects or critical hazards.

## 12 . Ecological information

- Environmental precautions** : No known significant effects or critical hazards.
- Products of degradation** : These products are carbon oxides (CO, CO<sub>2</sub>) and water.
- Toxicity of the products of biodegradation** : The products of degradation are less toxic than the product itself.

## 13 . Disposal considerations


- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.**

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Class	PG*	Label	Additional information
<b>TDG Classification</b>	1993 FLAMMABLE LIQUID, N.O.S. (EEP)	3	III		-

PG\* : Packing group

## 15 . Regulatory information

### United States

- HCS Classification** : Combustible liquid
- U.S. Federal regulations** : TSCA: No products were found.  
SARA 302/304/311/312 extremely hazardous substances: No products were found.  
SARA 302/304 emergency planning and notification: No products were found.  
SARA 302/304/311/312 hazardous chemicals: No products were found.  
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.  
Clean Water Act (CWA) 307: No products were found.  
Clean Water Act (CWA) 311: No products were found.  
Clean Air Act (CAA) 112 accidental release prevention: No products were found.  
Clean Air Act (CAA) 112 regulated flammable substances: No products were found.  
Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

**State regulations** : No products were found.

### Canada

- WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2B: Material causing other toxic effects (Toxic).

## 15 . Regulatory information

CEPA DSL: 100-137 EEP

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.


## 16 . Other information

**Label requirements** : COMBUSTIBLE LIQUID AND VAPOR.  
VAPOR MAY CAUSE FIRE.

**Hazardous Material Information System (U.S.A)** :

Health	1
Fire hazard	2
Reactivity	0
Personal protection	H

**National Fire Protection Association (U.S.A)** :



**References** : -Manufacturer's Material Safety Data Sheet.

**Date of printing** : 2/10/2006.

**Date of issue** : 2/1/2006.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.