

Material Safety Data Sheet

121-803 FAST THINNER

1. Product and company identification

Common name : 121-803 FAST THINNER
Synonym : FAST REDUCER
Material uses : Coatings: Solvent.
Manufacturer : Chemcraft International, Inc.
155 Rose Glen Road North
Port Hope, Ontario, Canada L1A 3Z3
Ph:905-885-6388 Fax:905-885-7587

Code : 121-803
MSDS # : Not available.
Validation date : **12/20/2005.**
Print date : 1/18/2006.
Responsible name : **A. Davis**
In case of emergency : 1-613-996-6666

2. Hazards identification

Physical state : Liquid.
Odor : Not available.
Emergency overview : Danger!
MAY BE FATAL IF ABSORBED THROUGH SKIN.
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS:
BLOOD, NERVOUS SYSTEM.
MAY BE HARMFUL IF SWALLOWED.
Do not ingest. Do not get in eyes or on skin or clothing. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes : No known significant effects or critical hazards.
Skin : Very toxic in contact with skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : Harmful if swallowed.

Potential chronic health effects : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [Acetic Acid, Ethyl Ester].
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.

Medical conditions aggravated by over-exposure : Repeated or prolonged exposure to the substance can produce target organs damage.
Over-exposure signs/symptoms : Not available.

See toxicological information (section 11)

3 . Composition/Information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Benzene, methyl-1-Butanol	108-88-3	50 - 70
Acetic Acid, Ethyl Ester	71-36-3	15 - 30
Acetic Acid, Butyl Ester	141-78-6	5 - 15
	123-86-4	5 - 15

4 . First aid measures

- Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

Antidote information

Product/ingredient name

Antidote information

Notes to physician : Not available.

5 . Fire-fighting measures

- Flammability of the product** : Flammable.
- Products of combustion** : These products are carbon oxides (CO, CO₂).
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Not available.
No specific hazard.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire Hazards in Presence of Various Substances** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
- Explosion Hazards in Presence of Various Substances** : Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

5 . Fire-fighting measures

:

6 . Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

7 . Handling and storage

- Handling** : Do not ingest. Do not get in eyes or on skin or clothing. Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.

8 . Exposure controls/personal protection

Product name

Acetic Acid, Ethyl Ester

Exposure limits

ACGIH TLV (United States).

TWA: 400 ppm 8 hour/hours.

ACGIH (United States).

TWA: 400 ppm

- Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control airborne levels. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protection

Eyes

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

- : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Other protection

- : Not available.

Personal protective equipment (Pictograms)

:

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9 . Physical and chemical properties

Physical state	: Liquid.
Flash point	: The lowest known value is Closed cup: -1°C (30.2°F). (Tagliabue). Open cup: -0.5°C (31.1°F). (Tagliabue). (Acetic Acid, Ethyl Ester)
Auto-ignition temperature	: The lowest known value is 343°C (649.4°F) (1-Butanol).
Flammable limits	: The greatest known range is Lower: 1.4% Upper: 11.2% (1-Butanol)
Color	: Not available.
Odor	: Not available.
Taste	: Not available.
Molecular weight	: Not applicable.
Molecular formula	: Not applicable.
pH	: Not available.
Boiling/condensation point	: The lowest known value is 77°C (170.6°F) (Acetic Acid, Ethyl Ester). Weighted average: 110.09°C (230.2°F)
Melting/freezing point	: May start to solidify at -77.9°C (-108.2°F) based on data for: Acetic Acid, Butyl Ester. Weighted average: -90.66°C (-131.2°F)
Critical temperature	: Not available.
Relative density	: Weighted average: 0.86 (Water = 1)
Vapor pressure	: The highest known value is 9.7 kPa (73 mm Hg) (at 20°C) (Acetic Acid, Ethyl Ester). Weighted average: 3.21 kPa (24.08 mm Hg) (at 20°C)
Vapor density	: The highest known value is 4 (Air = 1) (Acetic Acid, Butyl Ester). Weighted average: 3.11 (Air = 1)
Volatility	: Not available.
Odor threshold	: The lowest known value is 0.04 ppm (Acetic Acid, Butyl Ester)
Evaporation rate	: The highest known value is 7.5 (Acetic Acid, Ethyl Ester) Weighted average: 4.25 compared with Butyl acetate.
VOC	: Not available.
Viscosity	: Dynamic: The highest known value is 0.73 cP (Acetic Acid, Butyl Ester)
Ionicity (in water)	: Not available.
Dispersibility properties	: Partially dispersible in methanol, diethyl ether. Very slightly dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol.
Solubility	: Easily soluble in methanol, diethyl ether. Soluble in n-octanol. Very slightly soluble in cold water, hot water.
Physical/chemical properties comments	: Not available.

10 . Stability and reactivity

Stability and reactivity	: The product is stable.
Conditions of instability	: Not available.
Incompatibility with various substances	: Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis. Slightly reactive or incompatible with the following materials: organic materials and metals. Non-reactive or compatible with the following materials: moisture.
Hazardous decomposition products	: Not available.
Hazardous polymerization	: Not available.

10 . Stability and reactivity

- Conditions of reactivity** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

11 . Toxicological information

Toxicity data

- Chronic effects on humans** : **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [Acetic Acid, Ethyl Ester].
Contains material which causes damage to the following organs: blood, the nervous system.

- Other toxic effects on humans** : Very hazardous in case of skin contact (permeator), of ingestion, of inhalation.
Slightly hazardous in case of skin contact (irritant), of eye contact (irritant).

- Special remarks on toxicity to animals** : Not available.

- Special remarks on chronic effects on humans** : Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)

- Special remarks on other toxic effects on humans** : Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)

Specific effects

- Carcinogenic effects** : No known significant effects or critical hazards.

- Mutagenic effects** : No known significant effects or critical hazards.

- Teratogenicity / Reproductive toxicity** : No known significant effects or critical hazards.

Sensitization

- Ingestion** : No known significant effects or critical hazards.

- Inhalation** : No known significant effects or critical hazards.

- Eyes** : No known significant effects or critical hazards.

- Skin** : No known significant effects or critical hazards.

- Synergistic products** : Not available.

12 . Ecological information

Ecotoxicity data

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
--------------------------------	----------------	---------------	---------------

- Environmental precautions** : No known significant effects or critical hazards.

- Octanol/water partition coefficient** : The product is more soluble in octanol.

- Bioconcentration factor** : Not available.

- BOD and COD** : Not available.

- Biodegradable/OECD** : Not available.

- Mobility** : Not available.

- Products of degradation** : These products are carbon oxides (CO, CO₂) and water.

12. Ecological information

Toxicity of the products of biodegradation : The products of degradation are less toxic than the product itself.

Special remarks on the products of biodegradation : Not available.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste stream : Not available.


RCRA classification : Not available.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Class	PG*	Label	Additional information
TDG Classification	1263 PAINT RELATED MATERIAL	3	II		-

PG* : Packing group

15. Regulatory information

WHMIS (Canada) : Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).
Canadian Environmental Protection Act (CEPA): This product is on the Domestic Substances List (DSL) and is acceptable for use under the provisions of CEPA.: Acetic Acid, Butyl Ester

CEPA DSL: N-Butyl Alcohol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Toluene

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

EU regulations

Hazard symbol/symbols :



Risk phrases : R27- Very toxic in contact with skin.

15 . Regulatory information

- Safety phrases** : S1/2- Keep locked up and out of the reach of children.
S27/28- After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of [***].
S36/37- Wear suitable protective clothing and gloves.
S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

International regulations

- International lists** : Australia (NICNAS): Acetic Acid, Butyl Ester

16 . Other information

- References** : -Manufacturer's Material Safety Data Sheet.
- Other special considerations** : Not available.
- Date of printing** : 1/18/2006.
- Date of issue** : 12/20/2005.
- Version** : 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.