

# Material Safety Data Sheet

## Section 1. Product Identification and Use

Product Name - Trade Name **121-834 URETHANE REDUCER [CA 07174]**

Supplier - Manufacturer **Chemcraft International Inc.,**  
155 Rose Glen Road North  
P.O. Box 458  
Port Hope, ON.  
Canada L1A 3Z3  
Telephone (905) 885-6388 Fax (905) 885-5097  
**In case of Emergency** (905) 885-6388, (800) 263-7951

### For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 121-834  
Synonym URETHANE REDUCER [CA 07174]  
Chemical Name Not applicable.  
Chemical Family Reducing agent.  
Chemical Formula Not applicable.  
Material Uses Coatings: Surface coatings and finishes.  
Product Identification Number (PIN) 1263 PAINT RELATED MATERIAL

## Section 2. Hazardous Ingredients

### Exposure limits

Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>	TLV/PEL
Methyl n-amyl ketone	110-43-0	60-100	ORAL (LD50): Acute: 1670 mg/kg [Rat]. 730 mg/kg [Mouse]. DERMAL (LD50): Acute: 10220 mg/kg [Rabbit].	Not available.
Methyl isobutyl ketone	108-10-1	1-5	ORAL (LD50): Acute: 21000 mg/kg [Rat]. 2850 mg/kg [Mouse]. DERMAL (LD50): Acute: 20001 mg/kg [Rabbit].	<b>ACGIH (Canada, 1994).</b> TWA: 50 ppm STEL: 75 ppm TWA: 205 mg/m <sup>3</sup> STEL: 307 mg/m <sup>3</sup>

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

## Section 3. Physical Data

Physical State and Appearance Liquid.  
Color Light. Odor Not available. Taste Not available.  
Molecular Weight Not applicable.  
pH (1% soln/water) Not available.  
Boiling Point The lowest known value is 116°C (240.8°F) (2-Pentanone, 4-methyl-). Weighted average: 149.72°C (301.5°F)  
Melting Point May start to solidify at -33°C (-27.4°F) based on data for: 2-Heptanone. Weighted average: -35.5°C (-31.9°F)  
Critical Temperature Not available.  
Specific Gravity Weighted average: 0.82 (Water = 1)

Continued on Next Page

<b>Vapor Pressure</b>	The highest known value is 2 kPa (15 mm Hg) (at 20°C) (2-Pentanone, 4-methyl-). Weighted average: 0.39 kPa (2.93 mm Hg) (at 20°C)
<b>Vapor Density</b>	The highest known value is 3.94 (Air = 1) (2-Heptanone). Weighted average: 3.92 (Air = 1)
<b>Volatility</b>	Not available.
<b>Odor Threshold</b>	The lowest known value is 0.02 ppm (2-Heptanone) Weighted average: 0.02 ppm
<b>Water/Oil Dist. Coeff.</b>	Not available.
<b>Ionicity (in Water)</b>	Not available.
<b>Dispersion Properties</b>	See solubility in water, acetone.
<b>Solubility</b>	Easily soluble in acetone. Very slightly soluble in cold water, hot water.

## **Section 4. Fire and Explosion Hazard**

<b>The Product is:</b>	Flammable.
<b>Fire Hazards in Presence of Various Substances</b>	Highly flammable in presence of open flames, sparks and static discharge.
<b>Fire Fighting Media and Instructions</b>	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
<b>Special Remarks on Fire Hazards</b>	Not available.
<b>Flash Points</b>	The lowest known value is Closed cup: 16°C (60.8°F). (Tag Closed Cup). Open cup: 26°C (78.8°F). (Tagliabue). (2-Pentanone, 4-methyl-)
<b>Flammable Limits</b>	The greatest known range is Lower: 1.1% Upper: 7.9% (2-Heptanone)
<b>Auto-Ignition Temperature</b>	The lowest known value is 393°C (739.4°F) (2-Heptanone).
<b>Products of Combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ).
<b>Explosion Hazards in Presence of Various Substances</b>	Risks of explosion of the product in presence of mechanical impact: Not available. Highly explosive in presence of open flames, sparks and static discharge.
<b>Special Remarks on Explosion Hazards</b>	Not available.

## **Section 5. Reactivity Data**

<b>Stability</b>	The product is stable.
<b>Decomposition products</b>	Not available.
<b>Conditions of Instability</b>	Not available.
<b>Incompatibility with various substances</b>	Not available.
<b>Corrosivity</b>	Not available.
<b>Special Remarks on Reactivity</b>	Not available.
<b>Special Remarks on Corrosivity</b>	Not available.

## **Section 6. Toxicological Properties**

<b>Routes of Entry</b>	Dermal contact. Eye contact. Inhalation. Ingestion.
<b>Toxicity to Animals</b>	Acute oral toxicity (LD50): 758 mg/kg (Mouse) (Calculated value for the mixture). Acute dermal toxicity (LD50): 10476 mg/kg (Rabbit) (Calculated value for the mixture).
<b>Effects of Acute Exposure</b>	Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

<b>Chronic Effects on Humans</b>	<b>CARCINOGENIC EFFECTS:</b> Not available. <b>MUTAGENIC EFFECTS:</b> Not available. <b>TERATOGENIC EFFECTS:</b> Not available. <b>DEVELOPMENTAL TOXICITY:</b> Not available. The substance is toxic to kidneys, lungs, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
<b>Special Remarks on Toxicity to Animals</b>	Not available.
<b>Special Remarks on Chronic Effects on Humans</b>	Not available.
<b>Special Remarks on Other Toxic Effects on Humans</b>	Not available.
<b>Exposure Limits</b>	Not available.

## **Section 7. Preventive Measures**

<b>Personal Protection</b>	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
<b>Personal Protection in Case of a Large Spill</b>	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
<b>Engineering Controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
<b>Small Spill</b>	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
<b>Large Spill</b>	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.
<b>Waste Disposal</b>	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
<b>Precautions</b>	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.
<b>Storage</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
<b>TDG Classification</b>	3
<b>PIN</b>	1263 PAINT RELATED <b>PG: II</b> MATERIAL
<b>Special Provisions for Transport</b>	
<b>Federal and State Regulations</b>	SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Methyl Amyl Ketone SARA 313 toxic chemical notification and release reporting: 2-Pentanone, 4-methyl- 5% CERCLA: Hazardous substances.: 2-Pentanone, 4-methyl-;
<b>Other Regulations</b>	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).
<b>Other Classifications</b>	<b>WHMS (Canada)</b> <b>Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).</b> <b>Class D-2A: Material causing other toxic effects (VERY TOXIC).</b> <b>Class D-2B: Material causing other toxic effects (TOXIC).</b>  <b>HCS (U.S.A.)</b> Flammable liquid Class: Target organ effects.

<b>Hazardous Material Information System (U.S.A.)</b>	<b>Health Hazard</b>	* 2
	<b>Fire Hazard</b>	3
	<b>Reactivity</b>	0
	<b>Personal Protection</b>	H
<b>National Fire Protection Association (U.S.A.)</b>	<b>Health</b>	2
	<b>Fire Hazard</b>	3
	<b>Reactivity</b>	0
	<b>Specific Hazard</b>	

## **Section 8. First Aid Measures**

<b>Eye Contact</b>	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.
<b>Skin Contact</b>	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
<b>Hazardous Skin Contact</b>	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Hazardous Inhalation</b>	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
<b>Hazardous Ingestion</b>	Not available.

## **Section 9. Preparation Information**

<b>References</b>	-Manufacturers Material Safety Data Sheets.
<b>Other Special Considerations</b>	Not available.
<b>Related Information</b>	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
<b>Preparation Information</b>	<b>Validated by Alfreda Kowalski on 2/16/2005.</b> <b>Verified by Alfreda Kowalski.</b> <b>Printed 9/16/2005.</b>
<b>Information Contact</b>	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON, Canada. Phone: 905 885-6388 Fax: 905 885-5097

### **Notice to Reader**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*