

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **151-039 FLATTENING PASTE(CA07175)**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3
Telephone (905) 885-6388 Fax (905) 885-5097
In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 151-039
Synonym FLATTENING PASTE(CA07175)
Chemical Name Not applicable.
Chemical Family Synthetic polymer in organic solvent. (Paint.)
Chemical Formula Not applicable.
Material Uses Coatings: Surface coatings and finishes.
Product Identification Number (PIN) 1263 Paint

Section 2. Hazardous Ingredients

Exposure limits

| Name | CAS # | % by Weight | LC ₅₀ /LD ₅₀ | TLV/PEL |
|---------------------|-----------|-------------|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Toluene | 108-88-3 | 50 - 70 | ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit]. | ACGIH (United States, 1993). TWA: 50 ppm TWA: 188 mg/m ³ TWA: 200 ppm 8 hour/hours. |
| Methyl ethyl ketone | 78-93-3 | 15 - 30 | ORAL (LD50): Acute: 3000 mg/kg [Mouse]. 2737 mg/kg [Rat]. DERMAL (LD50): Acute: 6480 mg/kg [Rabbit]. | STEL: 300 ppm 15 minute/minutes. CEIL: 300 ppm |
| Silica, amorphous | 7631-86-9 | 5 - 15 | ORAL (LD50): Acute: 3160 mg/kg [Rat]. | OSHA (United States). TWA: 6 mg/m ³ |

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.
Color Not available. Odor Not available. Taste Not available.
Molecular Weight Not applicable.
pH (1% soln/water) Not applicable.
Boiling Point The lowest known value is 80°C (176°F) (2-Butanone). Weighted average: 101.45°C (214.6°F)
Melting Point May start to solidify at -85°C (-121°F) based on data for: 2-Butanone. Weighted average: -91.66°C (-133°F)
Critical Temperature Not available.

Continued on Next Page

(CA07175)

| | |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Specific Gravity | Weighted average: 0.85 (Water = 1) |
| Vapor Pressure | The highest known value is 10.3 kPa (77.5 mm Hg) (at 20°C) (2-Butanone). Weighted average: 5.11 kPa (38.33 mm Hg) (at 20°C) |
| Vapor Density | The highest known value is 3.14 (Air = 1) (Benzene, methyl-). Weighted average: 2.95 (Air = 1) |
| Volatility | Not available. |
| Odor Threshold | The lowest known value is 0.25 ppm (2-Butanone) |
| Water/Oil Dist. Coeff. | The product is much more soluble in octanol. |
| Ionicity (in Water) | Not available. |
| Dispersion Properties | Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone. |
| Solubility | Easily soluble in methanol, diethyl ether, acetone. Soluble in n-octanol. Insoluble in cold water, hot water. |

Section 4. Fire and Explosion Hazard

| | |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| The Product is: | Flammable. |
| Fire Hazards in Presence of Various Substances | Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Non-flammable in the presence of the following materials or conditions: heat, oxidizing materials, reducing materials, combustible materials and moisture. |
| Fire Fighting Media and Instructions | SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion. |
| Special Remarks on Fire Hazards | Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-) |
| Flash Points | The lowest known value is Closed cup: -6°C (21.2°F). (Tagliabue.). Open cup: -4°C (24.8°F). (2-Butanone) |
| Flammable Limits | The greatest known range is Lower: 1.8% Upper: 10% (2-Butanone) |
| Auto-Ignition Temperature | The lowest known value is 460°C (860°F) (2-Butanone). |
| Products of Combustion | These products are carbon oxides (CO, CO ₂). Some metallic oxides. |
| Explosion Hazards in Presence of Various Substances | Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge. |
| Special Remarks on Explosion Hazards | Not available. |

Section 5. Reactivity Data

| | |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stability | The product is stable. |
| Decomposition products | Not available. |
| Conditions of Instability | Not available. |
| Incompatibility with various substances | Slightly reactive or incompatible with the following materials: oxidizing materials, reducing materials, organic materials, metals, acids and alkalis. Non-reactive or compatible with the following materials: moisture. |
| Corrosivity | Not available. |
| Special Remarks on Reactivity | Incompatible with hydrogen fluoride. (Silica) |
| Special Remarks on Corrosivity | Not available. |

Section 6. Toxicological Properties

| | |
|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Routes of Entry | Dermal contact. Eye contact. Inhalation. Ingestion. |
| Toxicity to Animals | Acute oral toxicity (LD50): 2600 mg/kg [Rat.]. (Benzene, methyl-). Acute dermal toxicity (LD50): 6480 mg/kg [Rabbit]. (2-Butanone). Acute toxicity of the gas (LC50): 23500 mg/m ³ 8 hour/hours [Rat.]. (2-Butanone). Acute toxicity of the vapor (LC50): 32000 mg/m ³ 4 hour/hours [Mouse]. (2-Butanone). |
| Effects of Acute Exposure | Very hazardous in case of skin contact (permeator), of ingestion, of inhalation. |
| Chronic Effects on Humans | CARCINOGENIC EFFECTS: Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Butanone]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate any medical condition. |
| Special Remarks on Toxicity to Animals | Not available. |
| Special Remarks on Chronic Effects on Humans | Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-) |
| Special Remarks on Other Toxic Effects on Humans | Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-) |
| Exposure Limits | Not available. |

Section 7. Preventive Measures

| | |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal Protection | Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves. |
| Personal Protection in Case of a Large Spill | Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product. |
| Engineering Controls | Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Small Spill | Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container. |
| Large Spill | Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal. |
| Waste Disposal | Waste must be disposed of in accordance with federal, state and local environmental control regulations. |
| Precautions | Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. |
| Storage | Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). |
| TDG Classification | 3 |
| PIN | 1263 Paint PG: II |
| Special Provisions for Transport | - |

Continued on Next Page

(CA07175)**Federal and State Regulations**

WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Benzene; Benzene, methyl-

WARNING: This product contains chemical/chemicals known to the state of California to cause reproductive harm (male).: Benzene

WARNING: This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: Benzene; Benzene, methyl-

WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Benzene

Pennsylvania RTK: Benzene, methyl-

New Jersey: Benzene, methyl-

TSCA 8(b) inventory: Benzene, methyl-

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, methyl-: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Methyl Ethyl Ketone: Fire hazard, Immediate (acute) health hazard

CERCLA: Hazardous substances.: Benzene, methyl-: 1000 lbs. (453.6 kg); Methyl Ethyl Ketone;

Other Regulations

Not available. or of its ingredients

Other Classifications

WHMS (Canada) **Class B-2: Flammable liquid**
Class D-2B: Material causing other toxic effects (Toxic).

HCS (U.S.A.)

Hazardous Material Information System (U.S.A.)

| | |
|----------------------------|---|
| Health Hazard | 1 |
| Fire Hazard | 3 |
| Reactivity | 0 |
| Personal Protection | G |

National Fire Protection Association (U.S.A.)

| | |
|------------------------|---|
| Health | 1 |
| Fire Hazard | 3 |
| Reactivity | 0 |
| Specific Hazard | |

Section 8. First Aid Measures**Eye Contact**

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact

Wash with soap and water. Get medical attention if irritation develops.

Hazardous Skin Contact

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.

Hazardous Inhalation

Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion

Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Hazardous Ingestion

Not available.

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information Validated by K. William on 9/13/2006.

Verified by K. William.

Printed 12/19/2006.

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.