

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **194-245 CHEMCOLOUR MED YELLOW**

Supplier - Manufacturer **Chemcraft® International Inc.**

155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 194-245

Synonym CHEMCOLOUR MED YELLOW

Chemical Name Not applicable.

Chemical Family Coloring material.

Chemical Formula Not applicable.

Material Uses Coatings: Additives for surface coatings.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Low odour mineral spirits	64742-47-8	15 - 30	ORAL (LD50): Acute: 5000 mg/kg [Rat]. DERMAL (LD50): Acute: 3000 mg/kg [Rabbit].	TWA: 100 ppm ACGIH (United States). TWA: 525 mg/m ³
Propylene glycol monomethyl ether acetate	108-65-6	15 - 30	ORAL (LD50): Acute: 8532 mg/kg [Rat].	

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not applicable.

Boiling Point The lowest known value is 146°C (294.8°F) (2-Propanol, 1-methoxy, acetate). Weighted average: 180.59°C (357.1°F)

Melting Point May start to solidify at -58°C (-72.4°F) based on data for: Distillates (petroleum), hydrotreated light.

Critical Temperature Not available.

Specific Gravity Weighted average: 0.94 (Water = 1)

Vapor Pressure The highest known value is 0.3 kPa (2.4 mm Hg) (at 20°C) (2-Propanol, 1-methoxy, acetate).

Vapor Density The highest known value is 4.6 (Air = 1) (2-Propanol, 1-methoxy, acetate).

Continued on Next Page

Volatility	Not available.
Odor Threshold	Not available.
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in diethyl ether, n-octanol. Soluble in methanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion.
Special Remarks on Fire Hazards	Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back. (Distillates (petroleum), hydrotreated light)
Flash Points	The lowest known value is Closed cup: 47.2°C (117°F). (Pensky-Martens.). Open cup: 51.1°C (124°F). (Cleveland.). (2-Propanol, 1-methoxy, acetate)
Flammable Limits	The greatest known range is Lower: 1.3% Upper: 13.1% (2-Propanol, 1-methoxy, acetate)
Auto-Ignition Temperature	Not available.
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis. Slightly reactive or incompatible with the following materials: organic materials and metals. Non-reactive or compatible with the following materials: combustible materials and moisture.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 5000 mg/kg [Rat]. (Distillates (petroleum), hydrotreated light). Acute dermal toxicity (LD50): 3000 mg/kg [Rabbit]. (Distillates (petroleum), hydrotreated light).
Effects of Acute Exposure	Hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant, permeator), of eye contact (irritant).
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to blood, lungs, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (Distillates (petroleum), hydrotreated light)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Small Spill	Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: III
Special Provisions for Transport	-
Federal and State Regulations	No products were found.
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Continued on Next Page

Other Classifications	WHMIS (Canada)	Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). Class D-2B: Material causing other toxic effects (Toxic).
	HCS (U.S.A.)	Target organ effects Combustible liquid
Hazardous Material Information System (U.S.A.)	Health Hazard	* 1
	Fire Hazard	2
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	1
	Fire Hazard	2
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact	Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.
Hazardous Skin Contact	Not available.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by K. William on 7/17/2006. Verified by K. William. Printed 11/9/2007.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON, Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.