

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **194-439 CHEMCOLOR TINTER BURNT UMBER**

Supplier - Manufacturer **Chemcraft® International Inc.**

155 Rose Glen Road North

P.O. Box 458

Port Hope, ON.

Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 194-439

Synonym CHEMCOLOR TINTER BURNT UMBER

Chemical Name Not applicable.

Chemical Family Polymer in liquid. (Polymer.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Propylene glycol monomethyl ether acetate	108-65-6	30 - 50	ORAL (LD50): Acute: 8532 mg/kg [Rat].	
2-Methoxy-1-propanol acetate	70657-70-4	1 - 5	Not available.	
Silica quartz	14808-60-7	0.1 - 1	Not available.	

**ACGIH (United States).
Notes: Respirable
TWA: 0.1 mg/m³**

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not applicable.

Boiling Point The lowest known value is 146°C (294.8°F) (2-Propanol, 1-methoxy, acetate). Weighted average: 146°C (294.8°F)

Melting Point Not available.

Critical Temperature Not available.

Specific Gravity Weighted average: 1.01 (Water = 1)

Vapor Pressure The highest known value is 0.3 kPa (2.4 mm Hg) (at 20°C) (2-Propanol, 1-methoxy, acetate). Weighted average: 0.3 kPa (2.25 mm Hg) (at 20°C)

Vapor Density The highest known value is 4.6 (Air = 1) (2-Propanol, 1-methoxy, acetate). Weighted average: 4.6 (Air = 1)

Continued on Next Page

UMBER

Volatility	Not available.
Odor Threshold	Not available.
Water/Oil Dist. Coeff.	Not available.
Ionicity (in Water)	Not available.
Dispersion Properties	Not available.
Solubility	Insoluble in cold water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Never direct a water jet into the container in order to prevent any splashing of the product, which could cause the fire to spread. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion.
Special Remarks on Fire Hazards	Not available.
Flash Points	The lowest known value is Closed cup: 47.2°C (117°F). (Pensky-Martens.). Open cup: 51.1°C (124°F). (Cleveland.). (2-Propanol, 1-methoxy, acetate)
Flammable Limits	The greatest known range is Lower: 1.3% Upper: 13.1% (2-Propanol, 1-methoxy, acetate)
Auto-Ignition Temperature	Not available.
Products of Combustion	These products are carbon oxides (CO, CO ₂). Some metallic oxides.
Explosion Hazards in Presence of Various Substances	Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis. Non-reactive or compatible with the following materials: reducing materials, combustible materials, metals and moisture.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 8532 mg/kg [Rat]. (2-Propanol, 1-methoxy, acetate).
Effects of Acute Exposure	Hazardous in case of ingestion, of inhalation.

Continued on Next Page

UMBER

Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified 1 (Proven for humans.) by IARC, + (Proven.) by OSHA, + (Proven.) by NIOSH [Quartz (SiO ₂)]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to lungs. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	In laboratory inhalation studies, birth defects, increased foetal lethality and delayed foetal development have been observed in offspring of female animals, exposed during pregnancy, with a threshold response level in the range of 545 ppm concentration in the air. (1-Propanol, 2-methoxy-, acetate)
Special Remarks on Chronic Effects on Humans	Embryotoxic and/or foetotoxic in animal. (1-Propanol, 2-methoxy-, acetate)
Special Remarks on Other Toxic Effects on Humans	Crystalline silica has been shown to cause silicosis and lung cancer. Crystalline silica only causes these conditions when inhaled. (Quartz (SiO ₂))
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Small Spill	Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263PAINT PG: II
Special Provisions for Transport	-
Federal and State Regulations	WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Quartz (SiO ₂) WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Quartz (SiO ₂) SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Quartz (SiO ₂): Delayed (chronic) health hazard
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Continued on Next Page

UMBER

Other Classifications	WHMIS (Canada)	Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).
	HCS (U.S.A.)	Contains material which may cause cancer Target organ effects Combustible liquid
Hazardous Material Information System (U.S.A.)	Health Hazard	* 0
	Fire Hazard	2
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	2
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Hazardous Skin Contact	Not available.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by K. William on 1/25/2006. Verified by K. William. Printed 1/18/2007.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader***Continued on Next Page***

UMBER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.