

# Material Safety Data Sheet

## Section 1. Product Identification and Use

Product Name - Trade Name **251-011 WHITE WOOD PRIMER**

Supplier - Manufacturer **Chemcraft International Inc.,**  
155 Rose Glen Road North  
P.O. Box 458  
Port Hope, ON.  
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

**In case of Emergency** (905) 885-6388, (800) 263-7951

### For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 251-011

Synonym WHITE WOOD PRIMER

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

## Section 2. Hazardous Ingredients

### Exposure limits

Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>	TLV/PEL
Xylenes	1330-20-7	15 - 30	ORAL (LD50): Acute: 4300 mg/kg [Rat].	<b>ACGIH (United States, 1992).</b> TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m <sup>3</sup> STEL: 651 mg/m <sup>3</sup>
METHYL ETHYL KETONE	78-93-3	5 - 15	ORAL (LD50): Acute: 3400 mg/kg [Rat]. DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].	TWA: 200 ppm STEL: 300 ppm CEIL: 300 ppm <b>ACGIH (United States, 1993).</b> TWA: 590 mg/m <sup>3</sup> STEL: 585 mg/m <sup>3</sup> CEIL: 885 mg/m <sup>3</sup>
Isopropanol	67-63-0	5 - 15	ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog] . 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit].	<b>ACGIH (United States, 1994).</b> TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m <sup>3</sup> STEL: 1230 mg/m <sup>3</sup>
Ethyl Acetate	141-78-6	1 - 5	ORAL (LD50): Acute: 5620 mg/kg [Rat]. 4100 mg/kg [Mouse]. 4935 mg/kg [Rabbit]. DERMAL (LD50): Acute: >20 mg/kg [Rabbit].	<b>ACGIH TLV (United States)</b> TWA: 400 ppm 8 hour/hours. <b>ACGIH (United States).</b> TWA: 400 ppm
Toluene	108-88-3	1 - 5	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	<b>ACGIH (United States, 1993).</b> TWA: 50 ppm TWA: 188 mg/m <sup>3</sup>

Continued on Next Page

Methyl alcohol	67-56-1	1 - 5	ORAL (LD50): Acute: 6200 mg/kg [Rat]. 5600 mg/kg [Rat]. DERMAL (LD50): Acute: 15800 mg/kg [Rabbit].	<b>OSHA (United States).</b> TWA: 200 ppm <b>ACGIH (United States, 2000).</b> TWA: 200 ppm STEL: 250 ppm <b>NIOSH (1997).</b> TWA: 200 ppm STEL: 250 ppm TWA: 260 mg/m <sup>3</sup> STEL: 325 mg/m <sup>3</sup>
Ethyl 3-ethoxy propionate	763-69-9	1 - 5	ORAL (LD50): Acute: 5001 mg/kg [Rat]. 4301 mg/kg [Rat]. DERMAL (LD50): Acute: 10000 mg/kg [Rabbit]. VAPOR (LC50): Acute: >1000 ppm 6 hour/hours [Rat].	
Ethylbenzene	100-41-4	1 - 5	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	<b>ACGIH (United States).</b> TWA: 100 ppm STEL: 125 ppm <b>NIOSH</b> STEL: 125 ppm
Zinc Stearate	557-05-1	1 - 5	Not available.	<b>ACGIH (United States).</b> TWA: 10 mg/m <sup>3</sup> CEIL: 20 mg/m <sup>3</sup>

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

### Section 3. Physical Data

<b>Physical State and Appearance</b>	Liquid. (Viscous liquid.)
<b>Color</b>	Off-white.
<b>Odor</b>	Not available.
<b>Taste</b>	Not available.
<b>Molecular Weight</b>	Not applicable.
<b>pH (1% soln/water)</b>	Neutral.
<b>Boiling Point</b>	The lowest known value is 64.5°C (148.1°F) (Methanol). Weighted average: 117.55°C (243.6°F)
<b>Melting Point</b>	May start to solidify at <-50°C (-58°F) based on data for: Propanoic acid, 3-ethoxy-, ethyl ester. Weighted average: -81.29°C (-114.3°F)
<b>Critical Temperature</b>	Not available.
<b>Specific Gravity</b>	1.1 (Water = 1)
<b>Vapor Pressure</b>	The highest known value is 12.2 kPa (91.8 mm Hg) (at 20°C) (Methanol). Weighted average: 5.66 kPa (42.45 mm Hg) (at 20°C)
<b>Vapor Density</b>	The highest known value is 5.03 (Air = 1) (Propanoic acid, 3-ethoxy-, ethyl ester). Weighted average: 2.81 (Air = 1)
<b>Volatility</b>	Not available.
<b>Odor Threshold</b>	The lowest known value is 0.25 ppm (S151400 METHYL ETHYL KETONE) Weighted average: 3.46 ppm
<b>Water/Oil Dist. Coeff.</b>	The product is much more soluble in octanol.
<b>Ionicity (in Water)</b>	Not available.
<b>Dispersion Properties</b>	Partially dispersible in methanol, diethyl ether. Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
<b>Solubility</b>	Easily soluble in methanol, diethyl ether, n-octanol, acetone. Insoluble in cold water, hot water.

## Section 4. Fire and Explosion Hazard

<b>The Product is:</b>	Flammable.
<b>Fire Hazards in Presence of Various Substances</b>	Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Highly flammable in the presence of the following materials or conditions: heat.
<b>Fire Fighting Media and Instructions</b>	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Never direct a water jet into the container in order to prevent any splashing of the product, which could cause the fire to spread. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion.
<b>Special Remarks on Fire Hazards</b>	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, dimethyl-)
<b>Flash Points</b>	The lowest known value is Closed cup: -4°C (24.8°F). (Tagliabue.). Open cup: -9°C (15.8°F). (S151400 METHYL ETHYL KETONE)
<b>Flammable Limits</b>	The greatest known range is Lower: 6% Upper: 36.5% (Methanol)
<b>Auto-Ignition Temperature</b>	The lowest known value is 377°C (710.6°F) (Propanoic acid, 3-ethoxy-, ethyl ester).
<b>Products of Combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ). Some metallic oxides.
<b>Explosion Hazards in Presence of Various Substances</b>	Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and shocks and mechanical impacts.
<b>Special Remarks on Explosion Hazards</b>	Not available.

## Section 5. Reactivity Data

<b>Stability</b>	The product is stable.
<b>Decomposition products</b>	Not available.
<b>Conditions of Instability</b>	Not available.
<b>Incompatibility with various substances</b>	Highly reactive or incompatible with the following materials: oxidizing materials. Reactive or incompatible with the following materials: reducing materials, organic materials, metals, acids and alkalis. Non-reactive or compatible with the following materials: combustible materials and moisture.
<b>Corrosivity</b>	Not available.
<b>Special Remarks on Reactivity</b>	Incompatible with chlorinated compounds. (2-Propanol)
<b>Special Remarks on Corrosivity</b>	Not available.

## Section 6. Toxicological Properties

<b>Routes of Entry</b>	Dermal contact. Eye contact. Inhalation. Ingestion.
<b>Toxicity to Animals</b>	Acute oral toxicity (LD50): 2600 mg/kg [Rat]. (Benzene, methyl-). Acute dermal toxicity (LD50): >20 mg/kg [Rabbit]. (Acetic Acid, Ethyl Ester). Acute toxicity of the gas (LC50): 45000 mg/m <sup>3</sup> 2 hour/hours [Mouse]. (Acetic Acid, Ethyl Ester). Acute toxicity of the vapor (LC50): >1000 ppm 6 hour/hours [Rat]. (Propanoic acid, 3-ethoxy-, ethyl ester).
<b>Effects of Acute Exposure</b>	Very hazardous in case of ingestion. Hazardous in case of skin contact (permeator), of inhalation. Severe over-exposure can result in death.
<b>Chronic Effects on Humans</b>	Hazardous in case of inhalation. <b>CARCINOGENIC EFFECTS:</b> Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [S151400 METHYL ETHYL KETONE]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Titanium dioxide (TiO <sub>2</sub> )]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanol]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [Acetic Acid, Ethyl Ester]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [Methanol]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Octadecanoic acid, zinc salt]. <b>MUTAGENIC EFFECTS:</b> Not available.

Continued on Next Page

**TERATOGENIC EFFECTS:** Not available.

**DEVELOPMENTAL TOXICITY:** Not available.

The substance is toxic to the nervous system.

Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Not available.

**Special Remarks on Toxicity to Animals**

**Special Remarks on Chronic Effects on Humans**

Prolonged or repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea and central nervous system depression.

High level exposure to Xylene in laboratory animals, often at levels which are toxic to the mother, have affected the development of the fetus. The relevance of this to humans is not known. (Benzene, dimethyl-)

**Special Remarks on Other Toxic Effects on Humans**

Material is irritating to mucous membranes and upper respiratory tract. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. (Benzene, dimethyl-)

**Exposure Limits**

Not available.

## Section 7. Preventive Measures

**Personal Protection**

Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

**Personal Protection in Case of a Large Spill**

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.

**Engineering Controls**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.

**Small Spill**

Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.

**Large Spill**

Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal.

**Waste Disposal**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

**Precautions**

Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Take precautionary measures against electrostatic discharges. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.

**Storage**

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

**TDG Classification**

3

**PIN**

1263 PAINT

**PG:** II

**Special Provisions for Transport**

-

**Federal and State Regulations**

**WARNING:** This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Quartz (SiO<sub>2</sub>); Benzene; Benzene, methyl-

**WARNING:** This product contains chemical/chemicals known to the state of California to cause reproductive harm (male).: Benzene

**WARNING:** This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: Benzene; Benzene, methyl-

**WARNING:** This product contains chemical/chemicals known to the state of California to cause cancer.: Quartz (SiO<sub>2</sub>); Benzene

Illinois toxic substances disclosure to employee act: Benzene, ethyl-

New York release reporting list: Methanol; Acetic Acid, Ethyl Ester  
 New York acutely hazardous substances: Benzene, ethyl-  
 Rhode Island RTK hazardous substances: Benzene, ethyl-; Methanol; Acetic Acid, Ethyl Ester  
 Pennsylvania RTK: Benzene, dimethyl-; Benzene, ethyl-; 1,2-Propanediol; Methanol:  
 (environmental hazard); Isopropyl alcohol; Acetic Acid, Ethyl Ester; Benzene, methyl-  
 Florida: Benzene, ethyl-; Methanol; Acetic Acid, Ethyl Ester  
 Minnesota: Benzene, ethyl-; Methanol; Acetic Acid, Ethyl Ester  
 Massachusetts RTK: Benzene, ethyl-; Methanol; Isopropyl alcohol; Acetic Acid, Ethyl Ester  
 New Jersey: Benzene, ethyl-; Methanol; Isopropyl alcohol; Acetic Acid, Ethyl Ester; Benzene,  
 methyl-  
 TSCA 8(b) inventory: Benzene, dimethyl-; Benzene, ethyl-; Isopropyl alcohol; Acetic Acid,  
 Ethyl Ester; Benzene, methyl-  
 TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester  
 TSCA 8(d) H and S data reporting: Benzene, ethyl-  
 TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester  
 SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol  
 SARA 302/304/311/312 hazardous chemicals: Methanol  
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene,  
 dimethyl-: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard;  
 Benzene, ethyl-: Fire hazard, Immediate (acute) health hazard; 2-Propanol: Fire hazard,  
 Immediate (acute) health hazard, Delayed (chronic) health hazard; S151400 METHYL ETHYL  
 KETONE: Fire hazard, Immediate (acute) health hazard; Acetic Acid, Ethyl Ester: Fire hazard,  
 Immediate (acute) health hazard; Benzene, methyl-: Fire hazard, Immediate (acute) health  
 hazard, Delayed (chronic) health hazard  
 CERCLA: Hazardous substances.: Benzene, dimethyl-: 100 lbs. (45.36 kg); Benzene, ethyl-:  
 1000 lbs. (453.6 kg); Isobutyl alcohol; Methanol; S151400 METHYL ETHYL KETONE; Acetic  
 Acid, Ethyl Ester; Benzene, methyl-: 1000 lbs. (453.6 kg);  
 OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

**Other Regulations**

**Other Classifications**

**WHMIS (Canada)** **Class B-2: Flammable liquid**  
**Class D-1A: Material causing immediate and serious toxic effects (Very toxic).**  
**Class D-2A: Material causing other toxic effects (Very toxic).**  
**Class D-2B: Material causing other toxic effects (Toxic).**

**HCS (U.S.A.)** Contains material which may cause cancer  
 Highly toxic  
 Target organ effects

**Hazardous Material Information System (U.S.A.)**

<b>Health Hazard</b>	* 3
<b>Fire Hazard</b>	3
<b>Reactivity</b>	0
<b>Personal Protection</b>	G

**National Fire Protection Association (U.S.A.)**

<b>Health</b>	3
<b>Fire Hazard</b>	3
<b>Reactivity</b>	0
<b>Specific Hazard</b>	

**Section 8. First Aid Measures**

**Eye Contact** Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Skin Contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Hazardous Skin Contact** Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

**Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

<b>Hazardous Inhalation</b>	Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Warning: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
<b>Hazardous Ingestion</b>	Not available.

## **Section 9. Preparation Information**

<b>References</b>	-Manufacturers Material Safety Data Sheets.
<b>Other Special Considerations</b>	Not available.
<b>Related Information</b>	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
<b>Preparation Information</b>	<b>Validated by A. Davis on 12/21/2005.</b> <b>Verified by A. Davis.</b> <b>Printed 9/22/2006.</b>
<b>Information Contact</b>	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

### **Notice to Reader**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*