

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **312-069 CHEMTONE CLEAR**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 312-069

Synonym CHEMTONE CLEAR

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Polymer.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Toluene	108-88-3	30 - 50	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	ACGIH (Canada, 1993). TWA: 50 ppm TWA: 188 mg/m ³
Methyl isobutyl ketone	108-10-1	15 - 30	ORAL (LD50): Acute: 21000 mg/kg [Rat]. 2850 mg/kg [Mouse]. DERMAL (LD50): Acute: 20001 mg/kg [Rabbit].	ACGIH (Canada, 1994). TWA: 50 ppm STEL: 75 ppm TWA: 205 mg/m ³ STEL: 307 mg/m ³
Ethyl Acetate	141-78-6	5 - 15	ORAL (LD50): Acute: 5600 mg/kg [Rat].	ACGIH (Canada). TWA: 400 ppm
Acetone	67-64-1	5 - 15	ORAL (LD50): Acute: 5800 mg/kg [Rat]. DERMAL (LD50): Acute: 20000 mg/kg [Rabbit].	ACGIH (Canada, 1997). TWA: 500 ppm STEL: 750 ppm TWA: 1188 mg/m ³ STEL: 1782 mg/m ³
Ethyl alcohol	64-17-5	0.1 - 1	ORAL (LD50): Acute: 7060 mg/kg [Rat].	OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm
Potential additional emission of formaldehyde	50-00-0*	0.1 - 1	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit].	OSHA (Canada). STEL: 2 ppm TWA: 0.75 ppm

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Continued on Next Page

Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Not available.
Boiling Point	The lowest known value is 56.2°C (133.2°F) (2-Propanone). Weighted average: 101.75°C (215.2°F)
Melting Point	May start to solidify at -83°C (-117.4°F) based on data for: 2-Pentanone, 4-methyl-. Weighted average: -90.15°C (-130.3°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.89 (Water = 1)
Vapor Pressure	The highest known value is 24.1 kPa (181 mm Hg) (at 20°C) (2-Propanone). Weighted average: 5.52 kPa (41.4 mm Hg) (at 20°C)
Vapor Density	The highest known value is 3.5 (Air = 1) (2-Pentanone, 4-methyl-). Weighted average: 3.11 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.1 ppm (2-Pentanone, 4-methyl-) Weighted average: 0.59 ppm
Water/Oil Dist. Coeff.	The product is equally soluble in octanol and water.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersed in methanol, diethyl ether. See solubility in water, methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in methanol, diethyl ether. Soluble in cold water, hot water, n-octanol.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks and static discharge, of heat.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)
Flash Points	The lowest known value is Closed cup: -18°C (-0.4°F). (T.C.C.). (2-Propanone)
Flammable Limits	The greatest known range is Lower: 2.6% Upper: 12.8% (2-Propanone)
Auto-Ignition Temperature	The lowest known value is 448°C (838.4°F) (2-Pentanone, 4-methyl-).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Slightly reactive to reactive with oxidizing agents, reducing agents, organic materials, metals, acids, alkalis.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2600 mg/kg [Rat.]. (Benzene, methyl-). Acute dermal toxicity (LD50): 12210 mg/kg [Rabbit.]. (Benzene, methyl-). Acute toxicity of the vapor (LC50): 16000 ppm 4 hour(s) [Rat.]. (2-Propanone).
Effects of Acute Exposure	Very hazardous in case of skin contact (permeator), of ingestion, of inhalation.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for human or animal.) by EPA [2-Propanone]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Classified None. for human [2-Propanone]. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to blood, kidneys, lungs, the nervous system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
Special Remarks on Other Toxic Effects on Humans	Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.

Continued on Next Page

Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.	
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	
TDG Classification	3	
PIN	1263 PAINT	PG: II
Special Provisions for Transport	-	
Federal and State Regulations	<p>WARNING: This product contains chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm: Benzene, methyl-; Formaldehyde</p> <p>WARNING: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.: Benzene, methyl-</p> <p>WARNING: This product contains chemical(s) known to the State of California to cause cancer.: Formaldehyde</p> <p>New York release reporting list: Acetic Acid, Ethyl Ester</p> <p>Rhode Island RTK hazardous substances: Acetic Acid, Ethyl Ester</p> <p>Pennsylvania RTK: Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>Florida: Acetic Acid, Ethyl Ester</p> <p>Minnesota: Ethanol; Acetic Acid, Ethyl Ester</p> <p>Massachusetts RTK: Ethanol; Acetic Acid, Ethyl Ester</p> <p>New Jersey: Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>TSCA 8(b) inventory: Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, methyl-: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Acetic Acid, Ethyl Ester: Fire hazard, Immediate (Acute) Health Hazard</p> <p>CERCLA: Hazardous substances.: Benzene, methyl-: 1000 lbs. (453.6 kg); 2-Propanone: 5000 lbs. (2268 kg); Isobutyl alcohol; Acetic Acid, Ethyl Ester; 2-Pentanone, 4-methyl-;</p>	
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	WHMS (Canada)	<p>Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).</p> <p>Class D-2A: Material causing other toxic effects (VERY TOXIC).</p> <p>Class D-2B: Material causing other toxic effects (TOXIC).</p>
	HCS (U.S.A.)	Flammable liquid Irritating material Target organ effects
Hazardous Material Information System (U.S.A.)	Health Hazard	* 1
	Fire Hazard	3
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	0
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops. Cold water may be used.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by Florendo Tarnate on 9/16/2005. Verified by Florendo Tarnate. Printed 9/16/2005.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.