

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **350-010 CHEMLACK**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 **Fax** (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 350-010
Synonym CHEMLACK
Chemical Name Not applicable.
Chemical Family Synthetic polymer in organic solvent. (Paint.)
Chemical Formula Not applicable.
Material Uses Coatings: Surface coatings and finishes.
Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC₅₀/LD₅₀	TLV/PEL
Xylenes	1330-20-7	15 - 30	ORAL (LD50): Acute: 4300 mg/kg [Rat].	ACGIH (Canada, 1992). TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m ³ STEL: 651 mg/m ³
n-Butyl acetate	123-86-4	15 - 30	ORAL (LD50): Acute: 14130 mg/kg [Rat]. 7100 mg/kg [Mouse]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. 8770 mg/kg [Guinea pig].	OSHA (Canada). TWA: 150 ppm STEL: 200 ppm ACGIH (Canada, 2000). TWA: 150 ppm STEL: 200 ppm
Toluene	108-88-3	5 - 15	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	ACGIH (Canada, 1993). TWA: 50 ppm TWA: 188 mg/m ³
Ethyl alcohol	64-17-5	5 - 15	ORAL (LD50): Acute: 7060 mg/kg [Rat].	OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm
Isopropanol	67-63-0	5 - 15	ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog] . 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit].	ACGIH (Canada, 1994). TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m ³ STEL: 1230 mg/m ³
Ethylbenzene	100-41-4	5 - 15	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm
Ethyl 3-ethoxy propionate	763-69-9	1 - 5	ORAL (LD50): Acute: 5001 mg/kg [Rat]. 4301 mg/kg [Rat].	Not available.

Continued on Next Page

Silica, amorphous	7631-86-9	1 - 5	DERMAL (LD50): Acute: 10000 mg/kg [Rabbit]. VAPOR (LC50): Acute: >1000 ppm 6 hour(s) [Rat]. ORAL (LD50): Acute: 3160 mg/kg [Rat].	OSHA (Canada). TWA: 6 mg/m ³
-------------------	-----------	-------	--	---

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Neutral.
Boiling Point	The lowest known value is 78.5°C (173.3°F) (Ethanol). Weighted average: 129.55°C (265.2°F)
Melting Point	May start to solidify at -48°C (-54.4°F) based on data for: 1,2-Benzenedicarboxylic acid, di-C (8-10)-branched alkyl esters, C9-rich. Weighted average: -84.77°C (-120.6°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.93 (Water = 1)
Vapor Pressure	The highest known value is 5.7 kPa (43 mm Hg) (at 20°C) (Ethanol). Weighted average: 2.36 kPa (17.7 mm Hg) (at 20°C)
Vapor Density	The highest known value is 5.03 (Air = 1) (Propanoic acid, 3-ethoxy-, ethyl ester). Weighted average: 3.22 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.04 ppm (Acetic Acid, Butyl Ester) Weighted average: 28.56 ppm
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersed in methanol, diethyl ether. Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in methanol, diethyl ether, n-octanol, acetone. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge. Flammable in presence of heat.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, dimethyl-)
Flash Points	The lowest known value is Closed cup: 6°C (42.8°F). (Tagliabue). Open cup: 9°C (48.2°F). (Tagliabue). (Benzene, methyl-)
Flammable Limits	The greatest known range is Lower: 3.3% Upper: 19% (Ethanol)
Auto-Ignition Temperature	The lowest known value is 377°C (710.6°F) (Propanoic acid, 3-ethoxy-, ethyl ester).
Products of Combustion	These products are carbon oxides (CO, CO ₂). Some metallic oxides.
Explosion Hazards in Presence of Various Substances	Explosive in presence of open flames, sparks and static discharge, of shocks.

Continued on Next Page

Special Remarks on Explosion Hazards Not available.

Section 5. Reactivity Data

Stability The product is stable.

Decomposition products Not available.

Conditions of Instability Not available.

Incompatibility with various substances Reactive with oxidizing agents, reducing agents, alkalis. Slightly reactive to reactive with organic materials, metals, acids.

Corrosivity Not available.

Special Remarks on Reactivity Incompatible with chlorinated compounds. (2-Propanol)

Special Remarks on Corrosivity Not available.

Section 6. Toxicological Properties

Routes of Entry Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals Acute oral toxicity (LD50): 2600 mg/kg [Rat.]. (Benzene, methyl-).
Acute dermal toxicity (LD50): 5000 mg/kg [Rabbit]. (Acetic Acid, Butyl Ester).
Acute toxicity of the vapor (LC50): >1000 ppm 6 hour(s) [Rat.]. (Propanoic acid, 3-ethoxy-, ethyl ester).

Effects of Acute Exposure Hazardous in case of skin contact (permeator), of ingestion, of inhalation.

Chronic Effects on Humans **CARCINOGENIC EFFECTS:** Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester].
MUTAGENIC EFFECTS: Not available.
TERATOGENIC EFFECTS: Not available.
DEVELOPMENTAL TOXICITY: PROVEN [Ethanol]
The substance is toxic to blood, the nervous system, the reproductive system.
Repeated or prolonged exposure to the substance can produce target organs damage.

Special Remarks on Toxicity to Animals Not available.

Special Remarks on Chronic Effects on Humans Prolonged or repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea and central nervous system depression.
High level exposure to Xylene in laboratory animals, often at levels which are toxic to the mother, have affected the development of the fetus. The relevance of this to humans is not known. (Benzene, dimethyl-)

Special Remarks on Other Toxic Effects on Humans Material is irritating to mucous membranes and upper respiratory tract. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. (Benzene, dimethyl-)

Exposure Limits Not available.

Section 7. Preventive Measures

Personal Protection Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Small Spill Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Continued on Next Page

Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Take precautionary measures against electrostatic discharges. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	-
Federal and State Regulations	<p>WARNING: This product contains chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm: Benzene; Benzene, methyl-</p> <p>WARNING: This product contains chemical(s) known to the State of California to cause reproductive harm (male): Benzene</p> <p>WARNING: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.: Benzene; Benzene, methyl-</p> <p>WARNING: This product contains chemical(s) known to the State of California to cause cancer.: Benzene</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-; Acetic Acid, Ethyl Ester</p> <p>Pennsylvania RTK: Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester; Isopropyl alcohol; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester</p> <p>Florida: Benzene, ethyl-; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>Minnesota: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>Massachusetts RTK: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester; Isopropyl alcohol; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester</p> <p>New Jersey: Benzene, ethyl-; Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester; Isopropyl alcohol; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester</p> <p>TSCA 8(b) inventory: Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl-; Ethanol; Acetic Acid, Ethyl Ester; Isopropyl alcohol; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, ethyl-: Fire hazard, Immediate (Acute) Health Hazard; Benzene, dimethyl-: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Benzene, methyl-: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; 2-Propanol: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Acetic Acid, Butyl Ester</p> <p>CERCLA: Hazardous substances.: Benzene, ethyl-: 1000 lbs. (453.6 kg); Benzene, dimethyl-: 100 lbs. (45.36 kg); Benzene, methyl-: 1000 lbs. (453.6 kg); Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Isobutyl alcohol;</p>
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).
Other Classifications	<p>WHMIS (Canada)</p> <p>Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).</p> <p>Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).</p> <p>Class D-2A: Material causing other toxic effects (VERY TOXIC).</p> <p>Class D-2B: Material causing other toxic effects (TOXIC).</p> <p>HCS (U.S.A.) Flammable liquid Target organ effects</p>

Continued on Next Page

Hazardous Material Information System (U.S.A.)	Health Hazard	* 1
	Fire Hazard	3
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	0
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by Florendo Tarnate on 9/16/2005. Verified by Florendo Tarnate. Printed 9/16/2005.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.