

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **390-743 CHEMSEAL**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 390-743

Synonym CHEMSEAL

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			LC ₅₀ /LD ₅₀	TLV/PEL
Toluene	108-88-3	10-30	ORAL (LD50): Acute: 2600 mg/kg [Rat.]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	ACGIH (Canada, 1993). TWA: 50 ppm TWA: 188 mg/m ³ Not available.
1-Butanol	71-36-3	5-10	ORAL (LD50): Acute: 2510 mg/kg [Rat.]. 790 mg/kg [Rat]. DERMAL (LD50): Acute: 5300 mg/kg [Rabbit]. 3400 mg/kg [Rabbit].	Not available.
Ethylbenzene	100-41-4	1-5	ORAL (LD50): Acute: 3500 mg/kg [Rat.]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm Not available.
m-Methyltoluene	108-38-3	1-5	ORAL (LD50): Acute: 6750 mg/kg [Rat.]. DERMAL (LD50): Acute: 12400 mg/kg [Rabbit].	Not available.
o-Methyltoluene	95-47-6	1-5	ORAL (LD50): Acute: 3600 mg/kg [Rat.].	Not available.
p-Methyltoluene	106-42-3	1-5	ORAL (LD50): Acute: 4100 mg/kg [Rat.].	Not available.
Ethyl alcohol	64-17-5	5-10	ORAL (LD50): Acute: 7060 mg/kg [Rat.].	OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm
Ethyl Acetate	141-78-6	5-10	ORAL (LD50): Acute: 5600 mg/kg [Rat.].	OSHA (Canada). TWA: 400 ACGIH (Canada). TWA: 400 ppm
n-Butyl acetate	123-86-4	10-30	ORAL (LD50): Acute: 14130 mg/kg [Rat]. 7100 mg/kg [Mouse]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. 8770 mg/kg [Guinea pig].	OSHA (Canada). TWA: 150 ppm STEL: 200 ppm ACGIH (Canada, 2000). TWA: 150 ppm STEL: 200 ppm
Isopropanol	67-63-0	1-5	ORAL (LD50): Acute: 5045 mg/kg	ACGIH (Canada, 1994).

Continued on Next Page

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Avoid contact with oxidizing agents. (Benzene, (1-methylethenyl)-)
Incompatibility with various substances	Reactive with oxidizing agents. Slightly reactive to reactive with reducing agents, organic materials, acids, alkalis.
Corrosivity	Not available.
Special Remarks on Reactivity	Incompatible with chlorinated compounds. (2-Propanol)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 790 mg/kg [Rat]. (1-Butanol). Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit]. (1-Butanol). Acute toxicity of the vapor (LC50): >1800 ppm 4 hour(s) [Rat]. (Acetic Acid, Butyl Ester).
Effects of Acute Exposure	Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of skin contact (permeator), of ingestion, of inhalation. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [1-Butanol]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified 4 (Probably not for human.) by IARC [Silica gel, pptd., cryst.-free]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. The substance is toxic to blood, kidneys, the nervous system, the reproductive system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (Acetic Acid, Butyl Ester)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Continued on Next Page

Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Take precautionary measures against electrostatic discharges. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	
Federal and State Regulations	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Benzene, methyl-; Benzene, dimethyl-; Formaldehyde; Isobutyl alcohol; Formaldehyde</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene; Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene, methyl-; Benzene</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Benzene; Formaldehyde; Isobutyl alcohol; Formaldehyde</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Benzene, 1,3-dimethyl-; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-; Acetic Acid, Ethyl Ester</p> <p>Pennsylvania RTK: Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Silica gel, pptd., cryst.-free</p> <p>Florida: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>Minnesota: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Silica gel, pptd., cryst.-free</p> <p>Massachusetts RTK: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Silica gel, pptd., cryst.-free</p> <p>New Jersey: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Isopropyl alcohol</p> <p>TSCA 8(b) inventory: Benzene, methyl-; N-Butyl Alcohol; Benzene, dimethyl-; Ethanol; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Formaldehyde</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester</p> <p>SARA 302/304/311/312 extremely hazardous substances: N-Butyl Alcohol; Isopropyl alcohol; Formaldehyde</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Ethyl Ester: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Butyl Ester; Isobutyl alcohol: Fire Hazard, Immediate (Acute) Health Hazard</p> <p>SARA 313 toxic chemical notification and release reporting: Benzene, methyl- 11%; N-Butyl Alcohol 7.24625%; Benzene, dimethyl- 6%; Isopropyl alcohol 4.575%</p> <p>CERCLA: Hazardous substances.: Benzene, methyl-; N-Butyl Alcohol; Benzene, dimethyl-; Acetic Acid, Ethyl Ester; Acetic Acid, Butyl Ester; Isobutyl alcohol;</p>
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).
Other Classifications	<p>WHMIS (Canada)</p> <p>Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC). Class D-2B: Material causing other toxic effects (TOXIC).</p> <p>HCS (U.S.A.)</p> <p>Class: Highly toxic. Class: Flammable liquid having a flash point lower than 37.8°C (100°F). Class: Irritating substance. Class: Target organ effects.</p>

Hazardous Material Information System (U.S.A.)	Health Hazard	* 2
	Fire Hazard	3
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	3
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by C.M. Kelly on 11/5/2002. Verified by C.M. Kelly. Printed 3/3/2003.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.