

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **401-038 KNOT SEALER**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3
Telephone (905) 885-6388 Fax (905) 885-5097
In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 401-038
Synonym KNOT SEALER
Chemical Name Not applicable.
Chemical Family Synthetic polymer in organic solvent. (Paint.)
Chemical Formula Not applicable.
Material Uses Coatings: Surface coatings and finishes.
Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL ACGIH (United States, 1993).
Toluene	108-88-3	30 - 50	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	TWA: 50 ppm TWA: 188 mg/m ³
1-Butanol	71-36-3	15 - 30	ORAL (LD50): Acute: 2510 mg/kg [Rat]. 790 mg/kg [Rat]. DERMAL (LD50): Acute: 5300 mg/kg [Rabbit]. 3400 mg/kg [Rabbit]. VAPOR (LC50): Acute: 8000 mg/l 4 hour/hours [Rat].	TWA: 50 ppm CEIL: 50 ppm
Methyl isobutyl ketone	108-10-1	5 - 15	ORAL (LD50): Acute: 21000 mg/kg [Rat]. 2850 mg/kg [Mouse]. DERMAL (LD50): Acute: 20001 mg/kg [Rabbit].	ACGIH (United States, 1994). TWA: 50 ppm STEL: 75 ppm TWA: 205 mg/m ³ STEL: 307 mg/m ³
Isopropanol	67-63-0	5 - 15	ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog]. 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit].	ACGIH (United States, 1994). TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m ³ STEL: 1230 mg/m ³
Ethyl alcohol	64-17-5	5 - 15	ORAL (LD50): Acute: 7060 mg/kg [Rat]. VAPOR (LC50): Acute: 8000 mg/l 4 hour/hours [Rat].	OSHA (United States). TWA: 1000 ppm ACGIH (United States). TWA: 1000 ppm NIOSH TWA: 1000 ppm
Acetone	67-64-1	1 - 5	ORAL (LD50): Acute: 5800	ACGIH (United States,

Continued on Next Page

			mg/kg [Rat]. 3000 mg/kg [Mouse]. DERMAL (LD50): Acute: 20000 mg/kg [Rabbit].	1997). TWA: 500 ppm STEL: 750 ppm TWA: 1188 mg/m ³ STEL: 1782 mg/m ³
Isobutyl alcohol	78-83-1	1 - 5	ORAL (LD50): Acute: 2500 mg/kg [Rat.]. 3200 mg/kg [Mouse]. DERMAL (LD50): Acute: 4200 mg/kg [Rabbit.].	ACGIH (United States, 1993). TWA: 50 ppm
Xylenes	1330-20-7	0.1 - 1	ORAL (LD50): Acute: 4300 mg/kg [Rat.].	ACGIH (United States, 1992). TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m ³ STEL: 651 mg/m ³
Ethylbenzene	100-41-4	0.1 - 1	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	ACGIH (United States). TWA: 100 ppm STEL: 125 ppm NIOSH STEL: 125 ppm
Potential additional emission of formaldehyde	50-00-0*	0.1 - 1	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit].	OSHA (United States). STEL: 2 ppm TWA: 0.75 ppm

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Neutral.
Boiling Point	The lowest known value is 56.2°C (133.2°F) (2-Propanone). Weighted average: 105.45°C (221.8°F)
Melting Point	May start to solidify at -83°C (-117.4°F) based on data for: 2-Pentanone, 4-methyl-. Weighted average: -92.57°C (-134.6°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.87 (Water = 1)
Vapor Pressure	The highest known value is 24.1 kPa (181 mm Hg) (at 20°C) (2-Propanone). Weighted average: 3.86 kPa (28.95 mm Hg) (at 20°C)
Vapor Density	The highest known value is 3.5 (Air = 1) (2-Pentanone, 4-methyl-). Weighted average: 2.83 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.1 ppm (2-Pentanone, 4-methyl-) Weighted average: 36.17 ppm
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersible in methanol, diethyl ether. Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in methanol, diethyl ether, acetone. Soluble in n-octanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. Slightly flammable in the presence of the following materials or conditions: oxidizing materials.
Fire Fighting Media and Instructions	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)
Flash Points	The lowest known value is Closed cup: -18°C (-0.4°F). (T.C.C.). (2-Propanone)
Flammable Limits	The greatest known range is Lower: 3.3% Upper: 19% (Ethanol)
Auto-Ignition Temperature	The lowest known value is 343°C (649.4°F) (1-Butanol).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials, reducing materials and acids. Slightly reactive or incompatible with the following materials: organic materials, metals and alkalis. Non-reactive or compatible with the following materials: combustible materials and moisture.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 790 mg/kg [Rat]. (1-Butanol). Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit]. (1-Butanol). Acute toxicity of the gas (LC50): 44000 mg/m ³ 4 hour/hours [Mouse]. (2-Propanone). Acute toxicity of the vapor (LC50): 8000 mg/l 4 hour/hours [Rat.]. (1-Butanol).
Effects of Acute Exposure	Very hazardous in case of skin contact (permeator), of ingestion, of inhalation.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified A4 (Not classifiable for humans or animals.) by ACGIH [Ethanol]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for humans or animals.) by EPA [2-Propanone]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [Acetic Acid, Ethyl Ester]. Classified A2 (Suspected for humans.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Classified None. for humans [2-Propanone]. DEVELOPMENTAL TOXICITY: PROVEN [Ethanol] The substance is toxic to blood, kidneys, lungs, the nervous system, the reproductive system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.

Continued on Next Page

Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
Special Remarks on Other Toxic Effects on Humans	Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Small Spill	Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	-
Federal and State Regulations	<p>WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Benzene; Benzene, methyl-; Formaldehyde</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause reproductive harm (male).: Benzene</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: Benzene; Benzene, methyl-</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Benzene; Formaldehyde</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Ethyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Acetic Acid, Ethyl Ester; Benzene, ethyl-</p> <p>Pennsylvania RTK: Benzene, methyl-; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Benzene, ethyl-; Benzene, dimethyl-</p> <p>Florida: Acetic Acid, Ethyl Ester; Benzene, ethyl-</p> <p>Minnesota: Ethanol; Acetic Acid, Ethyl Ester; Benzene, ethyl-</p> <p>Massachusetts RTK: Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Benzene, ethyl-</p> <p>New Jersey: Benzene, methyl-; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Benzene, ethyl-</p>

Continued on Next Page

TSCA 8(b) inventory: N-Butyl Alcohol; Benzene, methyl-; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Benzene, ethyl-; Benzene, dimethyl-
 TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester
 TSCA 8(d) H and S data reporting: Benzene, ethyl-
 TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester
 SARA 302/304/311/312 extremely hazardous substances: N-Butyl Alcohol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, methyl-: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; 2-Propanol: Fire hazard, Delayed (chronic) health hazard; Isobutyl alcohol: Fire hazard, Delayed (chronic) health hazard
 CERCLA: Hazardous substances.: N-Butyl Alcohol; Benzene, methyl-: 1000 lbs. (453.6 kg); Acetic Acid, Ethyl Ester; 2-Propanone: 5000 lbs. (2268 kg); 2-Pentanone, 4-methyl-; Benzene, ethyl-: 1000 lbs. (453.6 kg); Benzene, dimethyl-: 100 lbs. (45.36 kg); Isobutyl alcohol;

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

OSHA: Standard for Occupational Exposure to Formaldehyde 29CFR 1910.1048 must be consulted before initial use of product

Other Classifications

WHMIS (Canada)	Class B-2: Flammable liquid
	Class D-2A: Material causing other toxic effects (Very toxic).
	Class D-2B: Material causing other toxic effects (Toxic).
HCS (U.S.A.)	Contains material which may cause cancer Target organ effects

Hazardous Material Information System (U.S.A.)	Health Hazard	* 2
	Fire Hazard	3
	Reactivity	0
	Personal Protection	G

National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	3
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
Hazardous Inhalation	Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information **Validated by S.Bice on 2/2/2006.**

Verified by S.Bice.

Printed 8/19/2006.

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.