

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **421-5065 DANCERYL 65 (C33846)**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 421-5065

Synonym DANCERYL 65 (C33846)

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure Limits

| Name | CAS # | % by Weight | LC ₅₀ /LD ₅₀ | TLV/PEL |
|---------------------------|----------|-------------|--|---|
| n-Butyl acetate | 123-86-4 | 10-30 | ORAL (LD50): Acute: 14130 mg/kg [Rat]. 7100 mg/kg [Mouse]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. 8770 mg/kg [Guinea pig]. | OSHA (Canada). TWA: 150 ppm STEL: 200 ppm ACGIH (Canada, 2000). TWA: 150 ppm STEL: 200 ppm |
| Formaldehyde | 50-00-0 | 0.1-1 | ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit]. | OSHA (Canada). STEL: 2 ppm TWA: 0.75 ppm Not available. |
| Ethyl 3-ethoxy propionate | 763-69-9 | 5-10 | ORAL (LD50): Acute: 5001 mg/kg [Rat]. 4301 mg/kg [Rat]. DERMAL (LD50): Acute: 10000 mg/kg [Rabbit]. VAPOR (LC50): Acute: >1000 ppm 6 hour(s) [Rat]. | ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm Not available. |
| Ethylbenzene | 100-41-4 | 1-5 | ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. | ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm Not available. |
| m-xylene | 108-38-3 | 5-10 | ORAL (LD50): Acute: 6750 mg/kg [Rat.]. DERMAL (LD50): Acute: 12400 mg/kg [Rabbit.]. | TWA: 100 ppm 8 hour(s). |
| o-xylene | 95-47-6 | 1-5 | ORAL (LD50): Acute: 3600 mg/kg [Rat.]. | TWA: 100 ppm 8 hour(s). |
| p-xylene | 106-42-3 | 1-5 | ORAL (LD50): Acute: 4100 mg/kg [Rat.]. | TWA: 100 ppm 8 hour(s). |
| Isopropanol | 67-63-0 | 1-5 | ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog]. 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit]. | ACGIH (Canada, 1994). TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m ³ STEL: 1230 mg/m ³ |
| 1-Butanol | 71-36-3 | 1-5 | ORAL (LD50): Acute: 2510 mg/kg [Rat.]. 790 mg/kg [Rat]. DERMAL (LD50): Acute: 5300 mg/kg [Rabbit.]. 3400 mg/kg | Not available. |

Continued on Next Page

| | | | | |
|---|----------|-------|---|---|
| Isobutyl alcohol | 78-83-1 | 1-5 | [Rabbit]. ORAL (LD50): Acute: 2500 mg/kg [Rat.]. 3200 mg/kg [Mouse]. DERMAL (LD50): Acute: 4200 mg/kg [Rabbit]. | ACGIH (Canada, 1993). TWA: 50 ppm |
| Ethyl alcohol | 64-17-5 | 1-5 | ORAL (LD50): Acute: 7060 mg/kg [Rat.]. | OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm |
| Potential additional emission of formaldehyde | 50-00-0* | 0.1-1 | ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit]. | OSHA (Canada). STEL: 2 ppm TWA: 0.75 ppm |

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

| | |
|--------------------------------------|---|
| Physical State and Appearance | Liquid. |
| Color | Not available. |
| Odor | Not available. |
| Taste | Not available. |
| Molecular Weight | Not applicable. |
| pH (1% soln/water) | Neutral. |
| Boiling Point | The lowest known value is 78.5°C (173.3°F) (Ethanol). Weighted average: 129.05°C (264.3°F) |
| Melting Point | May start to solidify at 13.3°C (55.9°F) based on data for: Benzene, 1,4-dimethyl-. Weighted average: -68.28°C (-90.9°F) |
| Critical Temperature | Not available. |
| Specific Gravity | Weighted average: 0.95 (Water = 1) |
| Vapor Pressure | The highest known value is 5.7 kPa (43 mmHg) (at 20°C) (Ethanol). Weighted average: 1.39 kPa (10.43 mmHg) (at 20°C) |
| Vapor Density | The highest known value is 5.03 (Air = 1) (Propanoic acid, 3-ethoxy-, ethyl ester). Weighted average: 3.75 (Air = 1) |
| Volatility | Not available. |
| Odor Threshold | The lowest known value is 0.04 ppm (Acetic Acid, Butyl Ester) Weighted average: 10.1 ppm |
| Water/Oil Dist. Coeff. | The product is more soluble in octanol. |
| Ionicity (in Water) | Not available. |
| Dispersion Properties | Is not dispersed in cold water, hot water, methanol. See solubility in methanol, diethyl ether, n-octanol, acetone. |
| Solubility | Easily soluble in methanol, diethyl ether, acetone. Partially soluble in n-octanol. Insoluble in cold water, hot water. |

Section 4. Fire and Explosion Hazard

| | |
|--|--|
| The Product is: | Flammable. |
| Fire Hazards in Presence of Various Substances | Highly flammable in presence of open flames, sparks and static discharge, of heat. |
| Fire Fighting Media and Instructions | SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion. |
| Special Remarks on Fire Hazards | Vapor may travel considerable distance to source of ignition and flash back. (Acetic Acid, Butyl Ester) |
| Flash Points | The lowest known value is Closed cup: 12.78°C (55°F). Open cup: 12.78°C (55°F). (Cleveland). (Ethanol) |
| Flammable Limits | The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol) |
| Auto-Ignition Temperature | The lowest known value is 343°C (649.4°F) (1-Butanol). |
| Products of Combustion | These products are carbon oxides (CO, CO2). |
| Explosion Hazards in Presence of Various Substances | Highly explosive in presence of open flames, sparks and static discharge. |

Continued on Next Page

Special Remarks on Explosion Hazards Not available.

Section 5. Reactivity Data

Stability The product is stable.

Decomposition products Not available.

Conditions of Instability Avoid contact with oxidizing agents. (Benzene, (1-methylethenyl)-)

Incompatibility with various substances Reactive with oxidizing agents, acids. Slightly reactive to reactive with reducing agents, alkalis.

Corrosivity Not available.

Special Remarks on Reactivity Incompatible with chlorinated compounds. (2-Propanol)

Special Remarks on Corrosivity Not available.

Section 6. Toxicological Properties

Routes of Entry Absorbed through skin. Eye contact. Inhalation. Ingestion.

Toxicity to Animals Acute oral toxicity (LD50): 790 mg/kg [Rat]. (1-Butanol).
Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit]. (1-Butanol).
Acute toxicity of the vapor (LC50): >1000 ppm 6 hour(s) [Rat]. (Propanoic acid, 3-ethoxy-, ethyl ester).

Effects of Acute Exposure Very hazardous in case of eye contact (irritant). Hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator). Inflammation of the eye is characterized by redness, watering, and itching.

Chronic Effects on Humans **CARCINOGENIC EFFECTS:** Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Propanoic acid, 3-ethoxy-, ethyl ester]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [1-Butanol]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde].

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde].

The substance is toxic to blood, kidneys, the nervous system, the reproductive system, liver.

Repeated or prolonged exposure to the substance can produce target organs damage.

Special Remarks on Toxicity to Animals Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)

Special Remarks on Chronic Effects on Humans 0347 Animal: embryotoxic, foetotoxic, passes through the placental barrier.

0900 Detected in maternal milk in human.

Narcotic effect; may cause nervous system disturbances. (Benzene, 1,3-dimethyl-)

Special Remarks on Other Toxic Effects on Humans Material is irritating to mucous membranes and upper respiratory tract. (Acetic Acid, Butyl Ester)

Exposure Limits Not available.

Section 7. Preventive Measures

Personal Protection Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices.

Personal Protection in Case of a Large Spill Splash goggles. Full suit. Vapor respirator. Boots. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Continued on Next Page

| | | |
|---|--|--|
| Small Spill | Absorb with an inert material and put the spilled material in an appropriate waste disposal. | |
| Large Spill | Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. | |
| Waste Disposal | Waste must be disposed of in accordance with federal, state and local environmental control regulations. | |
| Precautions | Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids. | |
| Storage | Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). | |
| TDG Classification | 3 | |
| PIN | 1263 PAINT | PG: II |
| Special Provisions for Transport | | |
| Federal and State Regulations | <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Formaldehyde; Benzene, dimethyl-; Dynomin UI-27-EI; Formaldehyde</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene; Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Formaldehyde; Benzene; Dynomin UI-27-EI; Formaldehyde</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Butyl Ester; Benzene, 1,3-dimethyl-</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-</p> <p>Pennsylvania RTK: Acetic Acid, Butyl Ester; Isopropyl alcohol; Ethanol</p> <p>Florida: Acetic Acid, Butyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-</p> <p>Minnesota: Acetic Acid, Butyl Ester; Benzene, ethyl-; Ethanol</p> <p>Massachusetts RTK: Acetic Acid, Butyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Isopropyl alcohol; Ethanol</p> <p>New Jersey: Acetic Acid, Butyl Ester; Benzene, ethyl-; Isopropyl alcohol; Ethanol</p> <p>TSCA 8(b) inventory: Acetic Acid, Butyl Ester; Formaldehyde; Benzene, dimethyl-; Isopropyl alcohol; N-Butyl Alcohol; Silica; Ethanol</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester</p> <p>SARA 302/304/311/312 extremely hazardous substances: Formaldehyde; Isopropyl alcohol; N-Butyl Alcohol</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Acetic Acid, Butyl Ester; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Dynomin UI-27-EI: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard</p> <p>SARA 313 toxic chemical notification and release reporting: Formaldehyde 0.125768%; Benzene, dimethyl- 13.6702%; Isopropyl alcohol 4.5%; N-Butyl Alcohol 3.09506%; Dynomin UI-27-EI 7.35%</p> <p>CERCLA: Hazardous substances.: Acetic Acid, Butyl Ester; Benzene, dimethyl-; N-Butyl Alcohol; Isobutyl alcohol;</p> | |
| Other Regulations | OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). | |
| Other Classifications | WHMIS (Canada) | Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC). Class D-2B: Material causing other toxic effects (TOXIC). |
| | HCS (U.S.A.) | Class: Highly toxic. Class: Flammable liquid having a flash point lower than 37.8°C (100°F). Class: Irritating substance. Class: Target organ effects. |

| | | |
|---|---------------------|-----|
| Hazardous Material Information System (U.S.A.) | Health Hazard | * 2 |
| | Fire Hazard | 3 |
| | Reactivity | 0 |
| | Personal Protection | H |
| National Fire Protection Association (U.S.A.) | Health | 2 |
| | Fire Hazard | 3 |
| | Reactivity | 0 |
| | Specific Hazard | |

Section 8. First Aid Measures

| | |
|-------------------------------|---|
| Eye Contact | Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin Contact | Wash with soap and water. Get medical attention if irritation develops. |
| Hazardous Skin Contact | Not available. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Hazardous Inhalation | Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention. |
| Ingestion | Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention. |
| Hazardous Ingestion | Not available. |

Section 9. Preparation Information

| | |
|-------------------------------------|---|
| References | -Manufacturers Material Safety Data Sheets. |
| Other Special Considerations | Not available. |
| Related Information | This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR. |
| Preparation Information | Validated by C.M. Kelly on 2/10/2003. Verified by C.M. Kelly. Printed 6/29/2004. |
| Information Contact | Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097 |

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.