

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **421-5535 PLASTOFIXSATIN(E05-0031)**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3
Telephone (905) 885-6388 Fax (905) 885-5097
In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 421-5535
Synonym PLASTOFIX SATIN(E05-0031)
Chemical Name Not applicable.
Chemical Family Synthetic polymer in organic solvent. (Paint.)
Chemical Formula Not applicable.
Material Uses Coatings: Surface coatings and finishes.
Product Identification Number (PIN) 1263 Paint

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Toluene	108-88-3	15 - 30	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	ACGIH (United States, 1993). TWA: 50 ppm TWA: 188 mg/m ³ TWA: 50 ppm CEIL: 50 ppm
1-Butanol	71-36-3	5 - 15	ORAL (LD50): Acute: 2510 mg/kg [Rat]. 790 mg/kg [Rat]. DERMAL (LD50): Acute: 5300 mg/kg [Rabbit]. 3400 mg/kg [Rabbit]. VAPOR (LC50): Acute: 8000 mg/l 4 hour/hours [Rat].	ACGIH (United States, 1992). TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m ³ STEL: 651 mg/m ³
Xylenes	1330-20-7	5 - 15	ORAL (LD50): Acute: 4300 mg/kg [Rat].	OSHA (United States). TWA: 1000 ppm ACGIH (United States). TWA: 1000 ppm NIOSH TWA: 1000 ppm
Ethyl alcohol	64-17-5	1 - 5	ORAL (LD50): Acute: 7060 mg/kg [Rat]. VAPOR (LC50): Acute: 8000 mg/l 4 hour/hours [Rat].	ACGIH (United States). TWA: 100 ppm STEL: 125 ppm NIOSH STEL: 125 ppm
Ethylbenzene	100-41-4	1 - 5	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	OSHA (United States). TWA: 6 mg/m ³
Silica, amorphous	7631-86-9	1 - 5	ORAL (LD50): Acute: 3160 mg/kg [Rat].	

Continued on Next Page

Potential additional emission of formaldehyde	50-00-0*	0.1 - 1	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit].	OSHA (United States). STEL: 2 ppm TWA: 0.75 ppm
Formaldehyde	50-00-0	0.1 - 1	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit]. VAPOR (LC50): Acute: 250 mg/l 4 hour/hours [Rat]. 590 mg/l 4 hour/hours [Rat].	OSHA (United States). STEL: 2 ppm 8 hour/hours. OSHA PEL (United States, 1995). TWA: 0.75 ppm OSHA action level (United States). TWA: 0.5 ppm 8 hour/hours.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Neutral.
Boiling Point	The lowest known value is 78.5°C (173.3°F) (Ethanol). Weighted average: 115.11°C (239.2°F)
Melting Point	May start to solidify at -89.5°C (-129.1°F) based on data for: 1-Butanol. Weighted average: -95°C (-139°F)
Critical Temperature	Not available.
Specific Gravity	0.9622 (Water = 1)
Vapor Pressure	The highest known value is 5.7 kPa (43 mm Hg) (at 20°C) (Ethanol). Weighted average: 2.15 kPa (16.13 mm Hg) (at 20°C)
Vapor Density	The highest known value is 3.7 (Air = 1) (Benzene, dimethyl-). Weighted average: 2.97 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.3 ppm (Benzene, dimethyl-) Weighted average: 54.09 ppm
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersible in methanol, diethyl ether. Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in methanol, diethyl ether, acetone. Soluble in n-octanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge. Flammable in the presence of the following materials or conditions: heat. Slightly flammable in the presence of the following materials or conditions: oxidizing materials. Non-flammable in the presence of the following materials or conditions: reducing materials, combustible materials and moisture.
Fire Fighting Media and Instructions	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray or fog. Cool containers with water jet in order to prevent pressure build-up, auto-ignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)

Continued on Next Page

Flash Points	The lowest known value is Closed cup: 6°C (42.8°F). (Tagliabue.). Open cup: 9°C (48.2°F). (Tagliabue). (Benzene, methyl-)
Flammable Limits	The greatest known range is Lower: 3.3% Upper: 19% (Ethanol)
Auto-Ignition Temperature	The lowest known value is 343°C (649.4°F) (1-Butanol).

Products of Combustion These products are carbon oxides (CO, CO₂). Some metallic oxides.

Explosion Hazards in Presence of Various Substances Highly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.

Special Remarks on Explosion Hazards Not available.

Section 5. Reactivity Data

Stability The product is stable.

Decomposition products Not available.

Conditions of Instability Not available.

Incompatibility with various substances Highly reactive or incompatible with the following materials: oxidizing materials.
Reactive or incompatible with the following materials: reducing materials, organic materials, metals and alkalis.
Slightly reactive or incompatible with the following materials: acids.
Non-reactive or compatible with the following materials: moisture.

Corrosivity Not available.

Special Remarks on Reactivity Incompatible with hydrogen fluoride. (Silica)

Special Remarks on Corrosivity Not available.

Section 6. Toxicological Properties

Routes of Entry Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals Acute oral toxicity (LD50): 790 mg/kg [Rat]. (1-Butanol).
Acute dermal toxicity (LD50): 3400 mg/kg [Rabbit]. (1-Butanol).
Acute toxicity of the vapor (LC50): 8000 mg/l 4 hour/hours [Rat]. (1-Butanol).

Effects of Acute Exposure Very hazardous in case of inhalation. Hazardous in case of skin contact (permeator), of ingestion.

Chronic Effects on Humans **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC, None. by OSHA [1-Butanol]. Classified A4 (Not classifiable for humans or animals.) by ACGIH [Ethanol]. Classified 1 (Proven for humans.) by IARC [Potential additional emission of formaldehyde]. Classified A2 (Suspected for humans.) by ACGIH, 2 (Reasonably anticipated to be human carcinogens.) by NTP [Potential additional emission of formaldehyde]. Classified A5 (Not suspected for humans.) by ACGIH, 4 (Probably not for humans.) by IARC [Acetic Acid, Ethyl Ester]. Classified 1 (Proven for humans.) by IARC [Formaldehyde]. Classified A2 (Suspected for humans.) by ACGIH, 2 (Reasonably anticipated to be human carcinogens.) by NTP [Formaldehyde].

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: PROVEN [Ethanol]

The substance is toxic to the nervous system, the reproductive system.

Repeated or prolonged exposure to the substance can produce target organs damage.

Special Remarks on Toxicity to Animals Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Potential additional emission of formaldehyde)

Special Remarks on Chronic Effects on Humans Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)

Special Remarks on Other Toxic Effects on Humans Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)

Exposure Limits Not available.

Continued on Next Page

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.	
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.	
Small Spill	Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.	
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not allow water to enter container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas. Dike if necessary. Call for assistance on disposal.	
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.	
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	
TDG Classification	3	
PIN	1263 Paint	PG: II
Special Provisions for Transport	-	
Federal and State Regulations	<p>WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Benzene, methyl-; Formaldehyde; Benzene</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause reproductive harm (male).: Benzene</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: Benzene, methyl-; Benzene</p> <p>WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Formaldehyde; Benzene</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Ethyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-; Acetic Acid, Ethyl Ester</p> <p>Pennsylvania RTK: Benzene, methyl-; Benzene, ethyl-; Benzene, dimethyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>Florida: Benzene, ethyl-; Acetic Acid, Ethyl Ester</p> <p>Minnesota: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>Massachusetts RTK: Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>New Jersey: Benzene, methyl-; Benzene, ethyl-; Ethanol; Acetic Acid, Ethyl Ester</p> <p>TSCA 8(b) inventory: Benzene, methyl-; Benzene, ethyl-; Benzene, dimethyl-; N-Butyl Alcohol; Ethanol; Acetic Acid, Ethyl Ester</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, methyl-: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Benzene, ethyl-: Fire hazard, Immediate (acute) health hazard; Benzene, dimethyl-: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard</p> <p>CERCLA: Hazardous substances.: Benzene, methyl-: 1000 lbs. (453.6 kg); Benzene, ethyl-: 1000 lbs. (453.6 kg); Benzene, dimethyl-: 100 lbs. (45.36 kg); N-Butyl Alcohol; Isobutyl alcohol; Acetic Acid, Ethyl Ester;</p>	

Continued on Next Page

Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
	OSHA: Standard for Occupational Exposure to Formaldehyde 29CFR 1910.1048 must be consulted before initial use of product	
Other Classifications	WHMIS (Canada)	Class B-2: Flammable liquid Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).
	HCS (U.S.A.)	Contains material which may cause cancer Target organ effects
Hazardous Material Information System (U.S.A.)	Health Hazard	* 2
	Fire Hazard	3
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	3
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
Hazardous Inhalation	Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by K. William on 11/2/2006. Verified by K. William. Printed 11/15/2006.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

Continued on Next Page

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.