

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **488-661 PLASTOFIX® LIGHT 50'**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 488-661

Synonym PLASTOFIX® LIGHT 50'

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			LC ₅₀ /LD ₅₀	TLV/PEL
Isobutyl acetate	110-19-0	5.4997	ORAL (LD50): Acute: 4763 mg/kg [Rabbit.]. 3200 mg/kg [Rat].	Not available.
Isopropanol	67-63-0	7.0018	ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog]. 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit].	ACGIH (Canada, 1994). TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m ³ STEL: 1230 mg/m ³
Ethyl Acetate	141-78-6	1.8802	ORAL (LD50): Acute: 5600 mg/kg [Rat].	OSHA (Canada). TWA: 400 ACGIH (Canada). TWA: 400 ppm
Ethylbenzene	100-41-4	1.1059	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm
m-Methyltoluene	108-38-3	2.7971	ORAL (LD50): Acute: 6750 mg/kg [Rat.]. DERMAL (LD50): Acute: 12400 mg/kg [Rabbit.].	Not available.
o-Methyltoluene	95-47-6	1.301	ORAL (LD50): Acute: 3600 mg/kg [Rat.].	Not available.
p-Methyltoluene	106-42-3	1.301	ORAL (LD50): Acute: 4100 mg/kg [Rat.].	Not available.
Formaldehyde	50-00-0	0.14798	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit].	OSHA (Canada). STEL: 2 ppm TWA: 0.75 ppm
Ethyl alcohol	64-17-5	12.963	ORAL (LD50): Acute: 7060 mg/kg [Rat.].	OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm
Potential additional emission of formaldehyde	50-00-0*	1.1692	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute: 270 mg/kg [Rabbit].	OSHA (Canada). STEL: 2 ppm TWA: 0.75 ppm
1-Butanol	71-36-3	7.7803	ORAL (LD50): Acute: 2510 mg/kg [Rat.]. 790 mg/kg [Rat].	Not available.

Continued on Next Page

Acetone	67-64-1	3.271	DERMAL (LD50): Acute: 5300 mg/kg [Rabbit]. 3400 mg/kg [Rabbit]. ORAL (LD50): Acute: 5800 mg/kg [Rat]. DERMAL (LD50): Acute: 20000 mg/kg [Rabbit].	ACGIH (Canada, 1997). TWA: 500 ppm STEL: 750 ppm TWA: 1188 mg/m ³ STEL: 1782 mg/m ³
Propylene glycol monomethyl ether acetate	108-65-6	1.292	ORAL (LD50): Acute: 8532 mg/kg [Rat].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Neutral.
Boiling Point	The lowest known value is 56.2°C (133.2°F) (2-Propanone). Weighted average: 99.17°C (210.5°F)
Melting Point	May start to solidify at 13.3°C (55.9°F) based on data for: Benzene, 1,4-dimethyl-. Weighted average: -90.31°C (-130.6°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.95 (Water = 1)
Vapor Pressure	The highest known value is 24.8 kPa (186.2 mmHg) (at 20°C) (2-Propanone). Weighted average: 4.84 kPa (36.3 mmHg) (at 20°C)
Vapor Density	The highest known value is 4.6 (Air = 1) (2-Propanol, 1-methoxy, acetate). Weighted average: 2.58 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.62 ppm (Benzene, 1,3-dimethyl-) Weighted average: 76.64 ppm
Water/Oil Dist. Coeff.	The product is more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersed in methanol, diethyl ether. Is not dispersed in cold water, hot water, n-octanol. See solubility in methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in methanol, diethyl ether. Partially soluble in n-octanol. Insoluble in cold water, hot water, acetone.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge. Flammable in presence of heat.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Containers should be grounded. (Ethanol)
Flash Points	The lowest known value is Closed cup: -18°C (-0.4°F). (T.C.C.). (2-Propanone)
Flammable Limits	The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol)
Auto-Ignition Temperature	The lowest known value is 343°C (649.4°F) (1-Butanol).
Products of Combustion	These products are carbon oxides (CO, CO ₂), nitrogen oxides (NO, NO ₂ ...).
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Highly explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Continued on Next Page

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents. Slightly reactive to reactive with reducing agents, acids, alkalis.
Corrosivity	Not available.
Special Remarks on Reactivity	Incompatible with chlorinated compounds. (2-Propanol)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 100 mg/kg [Rat]. (Formaldehyde). Acute dermal toxicity (LD50): 270 mg/kg [Rabbit]. (Formaldehyde). Acute toxicity of the vapor (LC50): 3500 ppm 4 hour(s) [Rat]. (Acetic acid, 2-methylpropyl ester).
Effects of Acute Exposure	Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of skin contact (sensitizer), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator). Severe over-exposure can result in death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified 4 (Probably not for human.) by IARC [Silica gel, pptd., cryst.-free]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [1-Butanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for human or animal.) by EPA [2-Propanone]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Classified None. for human [2-Propanone]. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. The substance is toxic to blood, kidneys, lungs, the nervous system, the reproductive system, liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.
Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Can cause gastrointestinal disturbances. (1-Butanol)
Special Remarks on Other Toxic Effects on Humans	Moderately toxic and narcotic in high concentrations. Experimentally tumorigen. (Ethanol)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Continued on Next Page

Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	
Federal and State Regulations	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Benzene, dimethyl-; Benzene, methyl-; Formaldehyde; Formaldehyde; Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene, methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Formaldehyde; Formaldehyde; Isobutyl alcohol</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Ethyl Ester; Benzene, 1,3-dimethyl-</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Acetic Acid, Ethyl Ester; Benzene, ethyl-</p> <p>Pennsylvania RTK: Acetic acid, 2-methylpropyl ester; Isopropyl alcohol; Acetic Acid, Ethyl Ester; Silica gel, pptd., cryst.-free; Ethanol</p> <p>Florida: Acetic Acid, Ethyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-</p> <p>Minnesota: Acetic Acid, Ethyl Ester; Benzene, ethyl-; Silica gel, pptd., cryst.-free; Ethanol</p> <p>Massachusetts RTK: Acetic acid, 2-methylpropyl ester; Isopropyl alcohol; Acetic Acid, Ethyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Silica gel, pptd., cryst.-free; Ethanol</p> <p>New Jersey: Acetic acid, 2-methylpropyl ester; Isopropyl alcohol; Acetic Acid, Ethyl Ester; Benzene, ethyl-; Ethanol</p> <p>TSCA 8(b) inventory: Acetic acid, 2-methylpropyl ester; Isopropyl alcohol; MPP-635 F; Acetic Acid, Ethyl Ester; Benzene, dimethyl-; Benzene, methyl-; Formaldehyde; Ethanol; N-Butyl Alcohol</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester</p> <p>SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol; Formaldehyde; N-Butyl Alcohol</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Acetic acid, 2-methylpropyl ester: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Ethyl Ester: Fire Hazard, Immediate (Acute) Health Hazard; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Isobutyl alcohol: Fire Hazard, Immediate (Acute) Health Hazard</p> <p>SARA 313 toxic chemical notification and release reporting: Isopropyl alcohol 7.00181%; 2-Pentanone, 4-methyl- 0.6375%; Benzene, dimethyl- 6.505%; Benzene, methyl- 0.82845%; Formaldehyde 0.147985%; N-Butyl Alcohol 7.78034%; 2-Propanone 3.271%</p> <p>CERCLA: Hazardous substances.: Acetic acid, 2-methylpropyl ester; 2-Pentanone, 4-methyl-; Acetic Acid, Ethyl Ester; Benzene, dimethyl-; Benzene, methyl-; N-Butyl Alcohol; 2-Propanone; Isobutyl alcohol;</p>
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications	WHMIS (Canada)	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-1B: Material causing immediate and serious toxic effects (TOXIC). Class D-2A: Material causing other toxic effects (VERY TOXIC). Class D-2B: Material causing other toxic effects (TOXIC).
	HCS (U.S.A.)	Class: Highly toxic. Class: Flammable liquid having a flash point lower than 37.8°C (100°F). Class: Irritating substance. Class: Target organ effects.
Hazardous Material Information System (U.S.A.)	Health Hazard	* 3
	Fire Hazard	3
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	3
	Fire Hazard	3
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by C.M. Kelly on 8/22/2002. Verified by C.M. Kelly. Printed 9/18/2002.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON, Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

Continued on Next Page

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.