

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **500-406 PERMATONE RED**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 **Fax** (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 500-406

Synonym PERMATONE RED

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Polymer.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC₅₀/LD₅₀	TLV/PEL
Methyl alcohol	67-56-1	50 - 70	ORAL (LD50): Acute: 6200 mg/kg [Rat]. 5600 mg/kg [Rat] . DERMAL (LD50): Acute: 15800 mg/kg [Rabbit].	OSHA (Canada). TWA: 200 ppm ACGIH (Canada, 2000). TWA: 200 ppm STEL: 250 ppm
Methyl ethyl ketone	78-93-3	30 - 50	ORAL (LD50): Acute: 3400 mg/kg [Rat]. DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].	TWA: 200 ppm 8 hour(s). STEL: 300 ppm 15 minute (s). CEIL: 300 ppm
Propylene glycol monomethyl ether	107-98-2	1 - 5	ORAL (LD50): Acute: 5660 mg/kg [Rat]. DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].	ACGIH (Canada). TWA: 100 ppm STEL: 150 ppm
Diethylene glycol monobutyl ether	112-34-5	1 - 5	ORAL (LD50): Acute: 6560 mg/kg [Rat]. 7292 mg/kg [Rat] . 5717 mg/kg [Rat]. DERMAL (LD50): Acute: 4120 mg/kg [Rabbit]. 2764 mg/kg [Rabbit]. 4040 mg/kg [Rabbit].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance	Liquid.				
Color	Not available.	Odor	Not available.	Taste	Not available.
Molecular Weight	Not applicable.				
pH (1% soln/water)	Neutral.				
Boiling Point	The lowest known value is 64.5°C (148.1°F) (Methanol). Weighted average: 74.41°C (165.9°F)				
Melting Point	May start to solidify at -68.1°C (-90.6°F) based on data for: Ethanol, 2-(2-butoxyethoxy)-. Weighted average: -92.9°C (-135.2°F)				
Critical Temperature	Not available.				
Specific Gravity	Weighted average: 0.81 (Water = 1)				
Vapor Pressure	The highest known value is 12.2 kPa (91.8 mm Hg) (at 20°C) (Methanol). Weighted average: 10.9 kPa (81.76 mm Hg) (at 20°C)				
Vapor Density	The highest known value is 5.6 (Air = 1) (Ethanol, 2-(2-butoxyethoxy)-). Weighted average: 1.74 (Air = 1)				
Volatility	Not available.				
Odor Threshold	The lowest known value is 0.25 ppm (2-Butanone)				
Water/Oil Dist. Coeff.	Not available.				
Ionicity (in Water)	Not available.				
Dispersion Properties	See solubility in water, methanol, diethyl ether, acetone.				
Solubility	Easily soluble in cold water, hot water, methanol, diethyl ether, acetone.				

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Explosive in the form of vapor when exposed to heat or flame. Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition, it emits acrid smoke and irritating fumes. (Methanol)
Flash Points	The lowest known value is Closed cup: -6°C (21.2°F). (Tagliabue.). Open cup: -4°C (24.8°F). (2-Butanone)
Flammable Limits	The greatest known range is Lower: 6% Upper: 36.5% (Methanol)
Auto-Ignition Temperature	The lowest known value is 227.78°C (442°F) (Ethanol, 2-(2-butoxyethoxy)-).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Highly explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Highly reactive with oxidizing agents. Slightly reactive to reactive with acids.

Continued on Next Page

Corrosivity	Not available.
Special Remarks on Reactivity	Air sensitive. (1-Propanol, 2-methoxy-)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3400 mg/kg [Rat]. (2-Butanone). Acute dermal toxicity (LD50): 2764 mg/kg [Rabbit]. (Ethanol, 2-(2-butoxyethoxy)-). Acute toxicity of the gas (LC50): 2000 ppm 4 hour(s) [Rat]. (2-Butanone). Acute toxicity of the vapor (LC50): 64000 ppm 4 hour(s) [Rat.]. (Methanol).
Effects of Acute Exposure	Extremely hazardous in case of ingestion. Very hazardous in case of skin contact (permeator). Hazardous in case of inhalation. Slightly hazardous in case of skin contact (irritant), of eye contact (irritant).
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [Methanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Butanone]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol, 1-methoxy-]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to blood, kidneys, the nervous system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	May be fatal or cause blindness if swallowed. Animal: embryotoxic, passes through the placental barrier. (Methanol)
Special Remarks on Other Toxic Effects on Humans	Narcotic. (Methanol)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.

Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	
TDG Classification	3	
PIN	1263 PAINT	PG: II
Special Provisions for Transport	-	
Federal and State Regulations	New York release reporting list: Methanol Rhode Island RTK hazardous substances: Methanol Pennsylvania RTK: Methanol: (environmental hazard); 2-Propanol, 1-methoxy-; Ethanol, 2-(2-butoxyethoxy)- Florida: Methanol Minnesota: Methanol Massachusetts RTK: Methanol; 2-Propanol, 1-methoxy- New Jersey: Methanol; 2-Propanol, 1-methoxy-; Ethanol, 2-(2-butoxyethoxy)- SARA 302/304/311/312 hazardous chemicals: Methanol SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Methyl ethyl ketone: Fire hazard, Immediate (Acute) Health Hazard CERCLA: Hazardous substances.: Methanol; Methyl ethyl ketone;	
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	WHMS (Canada)	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
	HCS (U.S.A.)	Flammable liquid Irritating material Target organ effects
Hazardous Material Information System (U.S.A.)	Health Hazard	* 1
	Fire Hazard	3
	Reactivity	0
	Personal Protection	G
National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	0
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention if irritation occurs.
Skin Contact	Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops. Cold water may be used.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information **Validated by Florendo Tarnate on 9/16/2005.**

Verified by Florendo Tarnate.

Printed 9/16/2005.

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.