

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **546-5143 E.S. SEALER (C33465)**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 546-5143

Synonym E.S. SEALER (C33465)

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure Limits

| Name | CAS # | % by Weight | LC ₅₀ /LD ₅₀ | TLV/PEL |
|----------------------------------|----------|-------------|---|---|
| Isopropanol | 67-63-0 | 1-5 | ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog]. 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit]. | ACGIH (Canada, 1994). TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m ³ STEL: 1230 mg/m ³ |
| Ethylbenzene | 100-41-4 | 5-10 | ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. | ACGIH (Canada). TWA: 100 ppm STEL: 125 ppm Not available. |
| m-Methyltoluene | 108-38-3 | 10-30 | ORAL (LD50): Acute: 6750 mg/kg [Rat.]. DERMAL (LD50): Acute: 12400 mg/kg [Rabbit.]. | Not available. |
| o-Methyltoluene | 95-47-6 | 5-10 | ORAL (LD50): Acute: 3600 mg/kg [Rat.]. | Not available. |
| p-Methyltoluene | 106-42-3 | 5-10 | ORAL (LD50): Acute: 4100 mg/kg [Rat.]. | Not available. |
| n-Butyl acetate | 123-86-4 | 10-30 | ORAL (LD50): Acute: 14130 mg/kg [Rat]. 7100 mg/kg [Mouse]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. 8770 mg/kg [Guinea pig]. | OSHA (Canada). TWA: 150 ppm STEL: 200 ppm ACGIH (Canada, 2000). TWA: 150 ppm STEL: 200 ppm |
| Ethyl 3-ethoxy propionate | 763-69-9 | 1-5 | ORAL (LD50): Acute: 5001 mg/kg [Rat]. 4301 mg/kg [Rat]. DERMAL (LD50): Acute: 10000 mg/kg [Rabbit]. VAPOR (LC50): Acute: >1000 ppm 6 hour(s) [Rat]. | Not available. |
| Isobutyl acetate | 110-19-0 | 10-30 | ORAL (LD50): Acute: 4763 mg/kg [Rabbit.]. 3200 mg/kg [Rat]. | Not available. |
| Ethyl alcohol | 64-17-5 | 5-10 | ORAL (LD50): Acute: 7060 mg/kg [Rat.]. | OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm |
| Potential additional emission of | 50-00-0* | 0.1-0.5 | ORAL (LD50): Acute: 100 mg/kg | OSHA (Canada). |

Continued on Next Page

formaldehyde

[Rat]. DERMAL (LD50): Acute:
270 mg/kg [Rabbit].STEL: 2 ppm
TWA: 0.75 ppm

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

| | |
|--------------------------------------|--|
| Physical State and Appearance | Liquid. |
| Color | Not available. |
| Odor | Not available. |
| Taste | Not available. |
| Molecular Weight | Not applicable. |
| pH (1% soln/water) | Neutral. |
| Boiling Point | The lowest known value is 78.5°C (173.3°F) (Ethanol). Weighted average: 128.01°C (262.4°F) |
| Melting Point | May start to solidify at 13.3°C (55.9°F) based on data for: Benzene, 1,4-dimethyl-. Weighted average: -67.76°C (-90°F) |
| Critical Temperature | Not available. |
| Specific Gravity | Weighted average: 0.93 (Water = 1) |
| Vapor Pressure | The highest known value is 5.7 kPa (43 mmHg) (at 20°C) (Ethanol). Weighted average: 1.9 kPa (14.25 mmHg) (at 20°C) |
| Vapor Density | The highest known value is 25 (Air = 1) (Paraplex G-62). Weighted average: 3.82 (Air = 1) |
| Volatility | Not available. |
| Odor Threshold | The lowest known value is 0.04 ppm (Acetic Acid, Butyl Ester) Weighted average: 30.05 ppm |
| Water/Oil Dist. Coeff. | The product is more soluble in octanol. |
| Ionicity (in Water) | Not available. |
| Dispersion Properties | Partially dispersed in methanol, diethyl ether. Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol. |
| Solubility | Easily soluble in methanol, diethyl ether. Partially soluble in n-octanol. Insoluble in cold water, hot water. |

Section 4. Fire and Explosion Hazard

| | |
|--|---|
| The Product is: | Flammable. |
| Fire Hazards in Presence of Various Substances | Highly flammable in presence of open flames, sparks and static discharge, of heat. |
| Fire Fighting Media and Instructions | SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion. |
| Special Remarks on Fire Hazards | Explosive in the form of vapor when exposed to heat or flame. Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits acrid smoke and irritating fumes. (Benzene, 1,3-dimethyl-) |
| Flash Points | The lowest known value is Closed cup: 12.78°C (55°F). Open cup: 12.78°C (55°F). (Cleveland). (Ethanol) |
| Flammable Limits | The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol) |
| Auto-Ignition Temperature | The lowest known value is 377°C (710.6°F) (Propanoic acid, 3-ethoxy-, ethyl ester). |
| Products of Combustion | These products are carbon oxides (CO, CO ₂). Some metallic oxides. |
| Explosion Hazards in Presence of Various Substances | Explosive in presence of open flames, sparks and static discharge, of shocks. |
| Special Remarks on Explosion Hazards | Not available. |

Continued on Next Page

Section 5. Reactivity Data

| | |
|--|--|
| Stability | The product is stable. |
| Decomposition products | Not available. |
| Conditions of Instability | Avoid contact with oxidizing agents. (Benzene, (1-methylethenyl)-) |
| Incompatibility with various substances | Reactive with oxidizing agents. Slightly reactive to reactive with reducing agents, acids, alkalis. |
| Corrosivity | Not available. |
| Special Remarks on Reactivity | Incompatible with chlorinated compounds. (2-Propanol) |
| Special Remarks on Corrosivity | Corrosive to ferrous metals and alloys. (Phosphoric acid) |

Section 6. Toxicological Properties

| | |
|---|---|
| Routes of Entry | Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion. |
| Toxicity to Animals | Acute oral toxicity (LD50): 3200 mg/kg [Rat]. (Acetic acid, 2-methylpropyl ester). Acute dermal toxicity (LD50): 5000 mg/kg [Rabbit]. (Benzene, ethyl-). Acute toxicity of the vapor (LC50): >1000 ppm 6 hour(s) [Rat]. (Propanoic acid, 3-ethoxy-, ethyl ester). |
| Effects of Acute Exposure | Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of skin contact (permeator), of ingestion, of inhalation. Slightly hazardous in case of skin contact (corrosive). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. |
| Chronic Effects on Humans | CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Propanoic acid, 3-ethoxy-, ethyl ester]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Phosphoric acid, monobutyl ester]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. The substance is toxic to blood, kidneys, the nervous system, the reproductive system, liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. |
| Special Remarks on Toxicity to Animals | Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde) |
| Special Remarks on Chronic Effects on Humans | 0347 Animal: embryotoxic, foetotoxic, passes through the placental barrier. 0900 Detected in maternal milk in human. Narcotic effect; may cause nervous system disturbances. (Benzene, 1,3-dimethyl-) |
| Special Remarks on Other Toxic Effects on Humans | Material is irritating to mucous membranes and upper respiratory tract. (Benzene, 1,3-dimethyl-) |
| Exposure Limits | Not available. |

Section 7. Preventive Measures

| | |
|---|--|
| Personal Protection | Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices. Boots. |
| Personal Protection in Case of a Large Spill | Splash goggles. Full suit. Vapor respirator. Boots. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. |
| Engineering Controls | Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location. |
| Small Spill | Absorb with an inert material and put the spilled material in an appropriate waste disposal. |
| Large Spill | Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. |
| Waste Disposal | Waste must be disposed of in accordance with federal, state and local environmental control regulations. |
| Precautions | Keep locked up. Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. Take precautionary measures against electrostatic discharges. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents. |
| Storage | Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). |
| TDG Classification | 3 |
| PIN | 1263 PAINT PG: II |
| Special Provisions for Transport | |
| Federal and State Regulations | <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: 2-Pyrrolidinone, 1-methyl-; Benzene, dimethyl-; Cymel UI-27-EI</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: 2-Pyrrolidinone, 1-methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Cymel UI-27-EI</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-; Acetic Acid, Ethyl Ester</p> <p>Pennsylvania RTK: Isopropyl alcohol; 2-Pyrrolidinone, 1-methyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Ethanol; Acetic Acid, Ethyl Ester</p> <p>Florida: 2-Pyrrolidinone, 1-methyl-; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester</p> <p>Minnesota: 2-Pyrrolidinone, 1-methyl-; Benzene, ethyl-; Acetic Acid, Butyl Ester; Ethanol; Acetic Acid, Ethyl Ester</p> <p>Massachusetts RTK: Isopropyl alcohol; 2-Pyrrolidinone, 1-methyl-; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Ethanol; Acetic Acid, Ethyl Ester</p> <p>New Jersey: Isopropyl alcohol; 2-Pyrrolidinone, 1-methyl-; Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Ethanol; Acetic Acid, Ethyl Ester</p> <p>TSCA 8(b) inventory: Isopropyl alcohol; 2-Pyrrolidinone, 1-methyl-; Benzene, dimethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Ethanol; Acetic Acid, Ethyl Ester; Formaldehyde; N-Butyl Alcohol</p> <p>TSCA 5(e) substance consent order: 2-Pyrrolidinone, 1-methyl-; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) one time export: 2-Pyrrolidinone, 1-methyl-</p> <p>TSCA 12(b) annual export notification: 2-Pyrrolidinone, 1-methyl-; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester</p> |

Continued on Next Page

SARA 302/304/311/312 extremely hazardous substances: Isopropyl alcohol; Formaldehyde; N-Butyl Alcohol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Ethyl Ester: Fire Hazard, Immediate (Acute) Health Hazard; Cymel UI-27-EI: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard
 SARA 313 toxic chemical notification and release reporting: Isopropyl alcohol 4.00234%; Benzene, dimethyl- 35.4609%; Cymel UI-27-EI 5.6%
 CERCLA: Hazardous substances.: 2-Pyrrolidinone, 1-methyl-; Benzene, dimethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Ethyl Ester; Isobutyl alcohol; N-Butyl Alcohol;
 OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Regulations**Other Classifications**

WHMIS (Canada)
Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).

HCS (U.S.A.)
 Class: Highly toxic.
 Class: Flammable liquid having a flash point lower than 37.8°C (100°F).
 Class: Target organ effects.
 Class: Corrosive material

| | | | |
|---|----------------------------|---|---|
| Hazardous Material Information System (U.S.A.) | Health Hazard | * | 3 |
| | Fire Hazard | | 3 |
| | Reactivity | | 0 |
| | Personal Protection | | |
| National Fire Protection Association (U.S.A.) | Health | | 3 |
| | Fire Hazard | | 3 |
| | Reactivity | | 0 |
| | Specific Hazard | | |

Section 8. First Aid Measures

| | |
|-------------------------------|---|
| Eye Contact | Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin Contact | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately. |
| Hazardous Skin Contact | Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Hazardous Inhalation | Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention. |
| Ingestion | Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention. |
| Hazardous Ingestion | Not available. |

Section 9. Preparation Information

| | |
|------------------------------|---|
| References | -Manufacturers Material Safety Data Sheets. |
| Other Special Considerations | Not available. |
| Related Information | This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR. |
| Preparation Information | Validated by C.M. Kelly on 6/7/2004. Verified by C.M. Kelly. Printed 9/8/2004. |
| Information Contact | Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097 |

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.