

# Material Safety Data Sheet

## Section 1. Product Identification and Use

Product Name - Trade Name **546-7153 RLS 573 CHEMTONE RIVERSTONE**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North  
P.O. Box 458  
Port Hope, ON.  
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

### For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 546-7153

Synonym RLS 573 CHEMTONE RIVERSTONE

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

## Section 2. Hazardous Ingredients

### Exposure Limits

Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>	TLV/PEL
Acetone	67-64-1	10-30	ORAL (LD50): Acute: 5800 mg/kg [Rat]. DERMAL (LD50): Acute: 20000 mg/kg [Rabbit].	<b>ACGIH (Canada, 1997).</b> TWA: 500 ppm STEL: 750 ppm TWA: 1188 mg/m <sup>3</sup> STEL: 1782 mg/m <sup>3</sup>
Methyl isobutyl ketone	108-10-1	10-30	ORAL (LD50): Acute: 21000 mg/kg [Rat]. 2850 mg/kg [Mouse]. DERMAL (LD50): Acute: 20001 mg/kg [Rabbit].	<b>ACGIH (Canada, 1994).</b> TWA: 50 ppm STEL: 75 ppm TWA: 205 mg/m <sup>3</sup> STEL: 307 mg/m <sup>3</sup>
Toluene	108-88-3	10-30	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	<b>ACGIH (Canada, 1993).</b> TWA: 50 ppm TWA: 188 mg/m <sup>3</sup>
Ethylbenzene	100-41-4	0.1-1	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	<b>ACGIH (Canada).</b> TWA: 100 ppm STEL: 125 ppm TWA: 100 ppm 8 hour(s).
p-xylene	106-42-3	0.1-1	ORAL (LD50): Acute: 4100 mg/kg [Rat].	
Isobutyl alcohol	78-83-1	1-5	ORAL (LD50): Acute: 2500 mg/kg [Rat]. 3200 mg/kg [Mouse]. DERMAL (LD50): Acute: 4200 mg/kg [Rabbit].	<b>ACGIH (Canada, 1993).</b> TWA: 50 ppm
Isopropanol	67-63-0	5-10	ORAL (LD50): Acute: 5045 mg/kg [Rat]. 4797 mg/kg [Dog]. 3600 mg/kg [Mouse]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit].	<b>ACGIH (Canada, 1994).</b> TWA: 400 ppm STEL: 500 ppm TWA: 983 mg/m <sup>3</sup> STEL: 1230 mg/m <sup>3</sup>
Ethyl alcohol	64-17-5	5-10	ORAL (LD50): Acute: 7060 mg/kg [Rat].	<b>OSHA (Canada).</b> TWA: 1000 ppm <b>ACGIH (Canada).</b> TWA: 1000 ppm
Potential additional emission of formaldehyde	50-00-0*	0.1-1	ORAL (LD50): Acute: 100 mg/kg [Rat]. DERMAL (LD50): Acute:	<b>OSHA (Canada).</b> STEL: 2 ppm

Continued on Next Page

270 mg/kg [Rabbit].

TWA: 0.75 ppm

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

### Section 3. Physical Data

<b>Physical State and Appearance</b>	Liquid.				
<b>Color</b>	Not available.	<b>Odor</b>	Not available.	<b>Taste</b>	Not available.
<b>Molecular Weight</b>	Not applicable.				
<b>pH (1% soln/water)</b>	Neutral.				
<b>Boiling Point</b>	The lowest known value is 56.2°C (133.2°F) (2-Propanone). Weighted average: 89.48°C (193.1°F)				
<b>Melting Point</b>	May start to solidify at -48°C (-54.4°F) based on data for: 1,2-Benzenedicarboxylic acid, di-C(8-10)-branched alkyl esters, C9-rich. Weighted average: -92.94°C (-135.3°F)				
<b>Critical Temperature</b>	Not available.				
<b>Specific Gravity</b>	Weighted average: 0.96 (Water = 1)				
<b>Vapor Pressure</b>	The highest known value is 24.1 kPa (181 mmHg) (at 20°C) (2-Propanone). Weighted average: 10.7 kPa (80.26 mmHg) (at 20°C)				
<b>Vapor Density</b>	The highest known value is 3.5 (Air = 1) (1,2-Benzenedicarboxylic acid, di-C(8-10)-branched alkyl esters, C9-rich). Weighted average: 2.56 (Air = 1)				
<b>Volatility</b>	Not available.				
<b>Odor Threshold</b>	The lowest known value is 0.1 ppm (2-Pentanone, 4-methyl-) Weighted average: 23.01 ppm				
<b>Water/Oil Dist. Coeff.</b>	The product is much more soluble in octanol.				
<b>Ionicity (in Water)</b>	Not available.				
<b>Dispersion Properties</b>	Very slightly dispersed in methanol, diethyl ether. Is not dispersed in cold water, hot water, n-octanol. See solubility in methanol, diethyl ether, n-octanol, acetone.				
<b>Solubility</b>	Easily soluble in methanol, diethyl ether, acetone. Soluble in n-octanol. Insoluble in cold water, hot water.				

### Section 4. Fire and Explosion Hazard

<b>The Product is:</b>	Flammable.
<b>Fire Hazards in Presence of Various Substances</b>	Highly flammable in presence of open flames, sparks and static discharge. Slightly flammable to flammable in presence of heat.
<b>Fire Fighting Media and Instructions</b>	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
<b>Special Remarks on Fire Hazards</b>	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)
<b>Flash Points</b>	The lowest known value is Closed cup: -18°C (-0.4°F). (T.C.C. ). (2-Propanone)
<b>Flammable Limits</b>	The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol)
<b>Auto-Ignition Temperature</b>	The lowest known value is 416°C (780.8°F) (1-Propanol, 2-methyl-).
<b>Products of Combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ). Some metallic oxides.
<b>Explosion Hazards in Presence of Various Substances</b>	Risks of explosion of the product in presence of mechanical impact: Not available. Highly explosive in presence of open flames, sparks and static discharge.
<b>Special Remarks on Explosion Hazards</b>	Not available.

Continued on Next Page

## Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Slightly reactive to reactive with oxidizing agents, reducing agents, acids, alkalis.
Corrosivity	Not available.
Special Remarks on Reactivity	Incompatible with chlorinated compounds. (2-Propanol)
Special Remarks on Corrosivity	Not available.

## Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2500 mg/kg [Rat.]. (1-Propanol, 2-methyl-). Acute dermal toxicity (LD50): 4200 mg/kg [Rabbit.]. (1-Propanol, 2-methyl-). Acute toxicity of the vapor (LC50): 8000 ppm 4 hour(s) [Rat.]. (Benzene, methyl-). Acute toxicity of the dust (LC50): >6820 mg/m <sup>3</sup> 4 hour(s) [Rat.]. (Titanium dioxide (TiO <sub>2</sub> )).
Effects of Acute Exposure	Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of skin contact (permeator), of ingestion, of inhalation. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Chronic Effects on Humans	<b>CARCINOGENIC EFFECTS:</b> Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanone]. Classified D (Not classifiable for human or animal.) by EPA [2-Propanone]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [Titanium dioxide (TiO <sub>2</sub> )]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [Carbon Black]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Propanol]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A2 (Suspected for human.) by ACGIH, 2A (Probable for human.) by IARC [Formaldehyde]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [Methanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [2-Butanone]. <b>MUTAGENIC EFFECTS:</b> Not available. <b>TERATOGENIC EFFECTS:</b> Classified None. for human [2-Propanone]. <b>DEVELOPMENTAL TOXICITY:</b> Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Formaldehyde]. The substance is toxic to blood, kidneys, lungs, the nervous system, the reproductive system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (2-Propanone)
Exposure Limits	Not available.

## Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Chemical resistant gloves, such as Norfoil should be used when handling this product. Please consult a Glove Manufacturer for alternate choices. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Continued on Next Page

<b>Small Spill</b>	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
<b>Large Spill</b>	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
<b>Waste Disposal</b>	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
<b>Precautions</b>	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.
<b>Storage</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
<b>TDG Classification</b>	3
<b>PIN</b>	1263 PAINT <b>PG: II</b>
<b>Special Provisions for Transport</b>	
<b>Federal and State Regulations</b>	California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Benzene; Benzene, methyl-; XYLENE; Benzene, ethyl-; 1-Propanol, 2-methyl-; Formaldehyde; Isobutyl alcohol; Formaldehyde California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: 1-Propanol, 2-methyl-; Isobutyl alcohol California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene; 1-Propanol, 2-methyl-; Isobutyl alcohol California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene; Benzene, methyl- California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Benzene; 1-Propanol, 2-methyl-; Formaldehyde; Isobutyl alcohol; Formaldehyde Illinois toxic substances disclosure to employee act: Benzene, ethyl- New York release reporting list: Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester; Methanol New York acutely hazardous substances: Benzene, ethyl- Rhode Island RTK hazardous substances: Benzene, ethyl-; Acetic Acid, Ethyl Ester; Methanol Pennsylvania RTK: Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Methanol: (environmental hazard) Florida: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester; Methanol Minnesota: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester; Ethanol; Acetic Acid, Ethyl Ester; Methanol Massachusetts RTK: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Methanol New Jersey: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Methanol TSCA 8(b) inventory: Benzene, methyl-; XYLENE; Benzene, ethyl-; Acetic Acid, Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Isopropyl alcohol; Ethanol; Acetic Acid, Ethyl Ester; Ethylene glycol monobutyl ether; Formaldehyde TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester TSCA 8(d) H and S data reporting: Benzene, ethyl- TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester SARA 302/304/311/312 extremely hazardous substances: 1-Butanol; Isopropyl alcohol; Formaldehyde SARA 302/304/311/312 hazardous chemicals: Methanol SARA 311/312 MSDS distribution - chemical inventory - hazard identification: XYLENE: Fire Hazard, Immediate (Acute) Health Hazard; Benzene, ethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Solvent naphtha (petroleum), light aliph.: Fire Hazard, Immediate (Acute) Health Hazard; 1-Propanol, 2-methyl-: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester: Fire Hazard, Immediate (Acute) Health Hazard; Ethylene glycol monobutyl ether: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Isobutyl alcohol: Fire Hazard, Immediate (Acute) Health Hazard; Methyl ethyl ketone: Fire Hazard, Immediate (Acute) Health Hazard SARA 313 toxic chemical notification and release reporting: 2-Propanone 23.595%; 2-Pentanone,

4-methyl- 14.0514%; Benzene, methyl- 15.0392%; XYLENE 1.36371%; Isopropyl alcohol 5.54%; Methanol 0.3866%; Methyl ethyl ketone 0.629385%  
 CERCLA: Hazardous substances.: 2-Propanone; 2-Pentanone, 4-methyl-; Benzene, methyl-; XYLENE; Benzene, ethyl-: 1000 lbs. (453.6 kg); 1-Propanol, 2-methyl-; Acetic Acid, Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester; Acetic Acid, Ethyl Ester; Isobutyl alcohol; Methanol; Methyl ethyl ketone;

**Other Regulations**

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

**Other Classifications**

**WHMIS (Canada)**      **Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).**  
**Class D-2A: Material causing other toxic effects (VERY TOXIC).**  
**Class D-2B: Material causing other toxic effects (TOXIC).**

**HCS (U.S.A.)**      Class: Flammable liquid having a flash point lower than 37.8°C (100°F).  
 Class: Irritating substance.  
 Class: Target organ effects.

**Hazardous Material Information System (U.S.A.)**

**Health Hazard**                      \*    2  
**Fire Hazard**                              3  
**Reactivity**                                0  
**Personal Protection**                H

**National Fire Protection Association (U.S.A.)**

**Health**                                        2  
**Fire Hazard**                                3  
**Reactivity**                                0  
**Specific Hazard**

**Section 8. First Aid Measures**

**Eye Contact**                              Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**Skin Contact**                              In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

**Hazardous Skin Contact**              Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

**Inhalation**                                 If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Hazardous Inhalation**                Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

**Ingestion**                                 Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

**Hazardous Ingestion**                 Not available.

**Section 9. Preparation Information**

**References**                                -Manufacturers Material Safety Data Sheets.

**Other Special Considerations**      Not available.

**Related Information**                 This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

**Preparation Information**            **Validated by C.M. Kelly on 2/25/2003.**  
**Verified by C.M. Kelly.**  
**Printed 5/12/2003.**

**Information Contact**

Prepared by the Health, Safety and Environment Department,  
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.  
Phone: 905 885-6388  
Fax: 905 885-5097

**Notice to Reader**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*