

# Material Safety Data Sheet

## Section 1. Product Identification and Use

Product Name - Trade Name **640-260 CHEMLITE SYSTEM B**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North  
P.O. Box 458  
Port Hope, ON.  
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

**In case of Emergency** (905) 885-6388, (800) 263-7951

### For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 640-260

Synonym CHEMLITE SYSTEM B

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

## Section 2. Hazardous Ingredients

### Exposure Limits

Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>	TLV/PEL
n-Butyl acetate	123-86-4	30-60	ORAL (LD50): Acute: 14130 mg/kg [Rat]. 7100 mg/kg [Mouse]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit]. 8770 mg/kg [Guinea pig].	<b>OSHA (Canada).</b> TWA: 150 ppm STEL: 200 ppm <b>ACGIH (Canada, 2000).</b> TWA: 150 ppm STEL: 200 ppm
Ethylbenzene	100-41-4	1-5	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	<b>ACGIH (Canada).</b> TWA: 100 ppm STEL: 125 ppm Not available.
m-xylene	108-38-3	1-5	ORAL (LD50): Acute: 6750 mg/kg [Rat]. DERMAL (LD50): Acute: 12400 mg/kg [Rabbit].	TWA: 100 ppm 8 hour(s).
o-xylene	95-47-6	1-5	ORAL (LD50): Acute: 3600 mg/kg [Rat].	TWA: 100 ppm 8 hour(s).
p-xylene	106-42-3	1-5	ORAL (LD50): Acute: 4100 mg/kg [Rat].	TWA: 100 ppm 8 hour(s).
Xylenes	1330-20-7	5-10	ORAL (LD50): Acute: 4300 mg/kg [Rat].	<b>ACGIH (Canada, 1992).</b> TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m <sup>3</sup> STEL: 651 mg/m <sup>3</sup>
Ethyl 3-ethoxy propionate	763-69-9	10-30	ORAL (LD50): Acute: 5001 mg/kg [Rat]. 4301 mg/kg [Rat]. DERMAL (LD50): Acute: 10000 mg/kg [Rabbit]. VAPOR (LC50): Acute: >1000 ppm 6 hour(s) [Rat].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

**Continued on Next Page**

### Section 3. Physical Data

Physical State and Appearance	Liquid.
Color	Not available.
Odor	Not available.
Taste	Not available.
Molecular Weight	Not applicable.
pH (1% soln/water)	Not applicable.
Boiling Point	The lowest known value is 126.5°C (259.7°F) (Acetic Acid, Butyl Ester). Weighted average: 135.81°C (276.5°F)
Melting Point	May start to solidify at 13.3°C (55.9°F) based on data for: Benzene, 1,4-dimethyl-. Weighted average: -67.2°C (-89°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.94 (Water = 1)
Vapor Pressure	The highest known value is 0.9 kPa (7.1 mmHg) (at 20°C) (Benzene, ethyl-). Weighted average: 0.53 kPa (3.98 mmHg) (at 20°C)
Vapor Density	The highest known value is 5.03 (Air = 1) (Propanoic acid, 3-ethoxy-, ethyl ester). Weighted average: 4.09 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.04 ppm (Acetic Acid, Butyl Ester) Weighted average: 0.17 ppm
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Is not dispersed in cold water, hot water, methanol. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in methanol, diethyl ether, acetone. Soluble in n-octanol. Insoluble in cold water, hot water.

### Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge, of heat.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Acetic Acid, Butyl Ester)
Flash Points	The lowest known value is Closed cup: 15°C (59°F). Open cup: 27°C (80.6°F). (Cleveland). (Benzene, ethyl-)
Flammable Limits	The greatest known range is LOWER: 1.1% UPPER: 7% (Benzene, 1,3-dimethyl-)
Auto-Ignition Temperature	The lowest known value is 377°C (710.6°F) (Propanoic acid, 3-ethoxy-, ethyl ester).
Products of Combustion	These products are carbon oxides (CO, CO <sub>2</sub> ).
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Highly explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

### Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents, reducing agents, acids, alkalis. Slightly reactive to reactive with organic materials, metals.
Corrosivity	Not available.

Continued on Next Page

Special Remarks on Reactivity	Incompatible with hydrogen fluoride. (Silica gel, pptd., cryst.-free)
Special Remarks on Corrosivity	Not available.

## Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3500 mg/kg [Rat]. (Benzene, ethyl-). Acute dermal toxicity (LD50): 5000 mg/kg [Rabbit]. (Acetic Acid, Butyl Ester). Acute toxicity of the vapor (LC50): >1000 ppm 6 hour(s) [Rat]. (Propanoic acid, 3-ethoxy-, ethyl ester).
Effects of Acute Exposure	Hazardous in case of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).
Chronic Effects on Humans	<b>CARCINOGENIC EFFECTS:</b> Classified A4 (Not classifiable for human or animal.) by ACGIH [Benzene, 1,3-dimethyl-]. Classified 4 (Probably not for human.) by IARC [Silica gel, pptd., cryst.-free]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Propanoic acid, 3-ethoxy-, ethyl ester]. <b>MUTAGENIC EFFECTS:</b> Not available. <b>TERATOGENIC EFFECTS:</b> Not available. <b>DEVELOPMENTAL TOXICITY:</b> Not available. The substance is toxic to blood, kidneys, the nervous system, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Formaldehyde has caused cancer in test animals at high concentrations (5-15 ppm). (Formaldehyde)
Special Remarks on Chronic Effects on Humans	Prolonged or repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea and central nervous system depression. High level exposure to Xylene in laboratory animals, often at levels which are toxic to the mother, have affected the development of the fetus. The relevance of this to humans is not known. (Benzene, dimethyl-)
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (Acetic Acid, Butyl Ester)
Exposure Limits	Not available.

## Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, acids, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT
PG:	II
Special Provisions for Transport	

Continued on Next Page

<b>Federal and State Regulations</b>	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: XYLENE; Benzene, dimethyl-; Formaldehyde</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Benzene; Formaldehyde</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Acetic Acid, Butyl Ester; Benzene, 1,3-dimethyl-</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-</p> <p>Pennsylvania RTK: Acetic Acid, Butyl Ester; Silica gel, pptd., cryst.-free</p> <p>Florida: Acetic Acid, Butyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-</p> <p>Minnesota: Acetic Acid, Butyl Ester; Benzene, ethyl-; Silica gel, pptd., cryst.-free</p> <p>Massachusetts RTK: Acetic Acid, Butyl Ester; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Silica gel, pptd., cryst.-free</p> <p>New Jersey: Acetic Acid, Butyl Ester; Benzene, ethyl-</p> <p>TSCA 8(b) inventory: Acetic Acid, Butyl Ester; XYLENE; Benzene, dimethyl-; Formaldehyde</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester</p> <p>SARA 302/304/311/312 extremely hazardous substances: Formaldehyde</p> <p>SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Acetic Acid, Butyl Ester; XYLENE: Fire Hazard, Immediate (Acute) Health Hazard; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard</p> <p>SARA 313 toxic chemical notification and release reporting: XYLENE 9.2305%; Benzene, dimethyl- 8.9975%</p> <p>CERCLA: Hazardous substances.: Acetic Acid, Butyl Ester; XYLENE; Benzene, dimethyl-;</p>	
<b>Other Regulations</b>	<p>OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).</p>	
<b>Other Classifications</b>	<b>WHMIS (Canada)</b>	<p><b>Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).</b></p> <p><b>Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).</b></p> <p><b>Class D-2A: Material causing other toxic effects (VERY TOXIC).</b></p> <p><b>Class D-2B: Material causing other toxic effects (TOXIC).</b></p>
	<b>HCS (U.S.A.)</b>	<p>Class: Highly toxic.</p> <p>Class: Flammable liquid having a flash point lower than 37.8°C (100°F).</p> <p>Class: Target organ effects.</p>

<b>Hazardous Material Information System (U.S.A.)</b>	<b>Health Hazard</b>	*	2
	<b>Fire Hazard</b>		3
	<b>Reactivity</b>		0
	<b>Personal Protection</b>		H
<b>National Fire Protection Association (U.S.A.)</b>	<b>Health</b>		2
	<b>Fire Hazard</b>		3
	<b>Reactivity</b>		0
	<b>Specific Hazard</b>		

## Section 8. First Aid Measures

<b>Eye Contact</b>	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash with soap and water. Get medical attention if irritation develops.
<b>Hazardous Skin Contact</b>	Not available.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

<b>Hazardous Inhalation</b>	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. <b>WARNING:</b> It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
<b>Hazardous Ingestion</b>	Not available.

## **Section 9. Preparation Information**

<b>References</b>	-Manufacturers Material Safety Data Sheets.
<b>Other Special Considerations</b>	Not available.
<b>Related Information</b>	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
<b>Preparation Information</b>	<b>Validated by C.M. Kelly on 3/27/2003.</b> <b>Verified by C.M. Kelly.</b> <b>Printed 4/15/2003.</b>
<b>Information Contact</b>	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

### **Notice to Reader**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*