

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **825-4538 RLS 634 CHEMGLAZE (C29532)**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 825-4538

Synonym RLS 634 CHEMGLAZE (C29532)

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure Limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Heavy naphtha, hydrotreated	64742-48-9	60-100	Not available.	Not available.
Ferric oxide	1309-37-1	1-5	Not available.	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not applicable.

Boiling Point The lowest known value is 93°C (199.4°F) (Naphtha (petroleum), hydrotreated heavy).

Melting Point Not available.

Critical Temperature Not available.

Specific Gravity Weighted average: 0.84 (Water = 1)

Vapor Pressure Not available.

Vapor Density The highest known value is 3.45 (Air = 1) (Naphtha (petroleum), hydrotreated heavy).

Volatility Not available.

Odor Threshold Not available.

Water/Oil Dist. Coeff. The product is much more soluble in octanol.

Ionicity (in Water) Not available.

Continued on Next Page

Dispersion Properties	Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in diethyl ether, n-octanol, acetone. Partially soluble in methanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Extremely flammable in presence of open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Naphtha (petroleum), hydrotreated heavy)
Flash Points	The lowest known value is Closed cup: -4°C (24.8°F). (Tagliabue.). (Naphtha (petroleum), hydrotreated heavy)
Flammable Limits	The greatest known range is LOWER: 1% UPPER: 6% (Naphtha (petroleum), hydrotreated heavy)
Auto-Ignition Temperature	The lowest known value is 254°C (489.2°F) (Naphtha (petroleum), hydrotreated heavy).
Products of Combustion	These products are carbon oxides (CO, CO ₂). Some metallic oxides.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Extremely explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents, reducing agents, organic materials, acids, alkalis. Slightly reactive to reactive with metals.
Corrosivity	Not available.
Special Remarks on Reactivity	Incompatible with peroxides. (Benzene)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 10001 mg/kg [Rat]. (Cyclohexanone, homopolymer).
Effects of Acute Exposure	Very hazardous in case of skin contact (irritant). Hazardous in case of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC, None. by OSHA [1-Butanol]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [Carbon Black]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to kidneys, liver. Repeated or prolonged exposure to the substance can produce target organs damage.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Carbon black contains trace amounts absorbed polynuclear aromatic compounds (PAH), some of which have been found to be carcinogens in animal studies. Carbon black has not been shown to cause cancer in humans or animals. (Carbon Black)

Continued on Next Page

Special Remarks on Other Toxic Effects on Humans	Moderately toxic and narcotic in high concentrations. (Naphtha (petroleum), hydrotreated heavy)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, acids, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	
Federal and State Regulations	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Quartz (SiO₂); Benzene, dimethyl-; 1-Propanol, 2-methyl-; Benzene, methyl-; Isobutyl alcohol; Benzene, dimethyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Quartz (SiO₂); 1-Propanol, 2-methyl-; Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Quartz (SiO₂); Benzene; 1-Propanol, 2-methyl-; Isobutyl alcohol</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene; Benzene, methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Benzene; 1-Propanol, 2-methyl-; Isobutyl alcohol</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p> <p>Rhode Island RTK hazardous substances: Benzene, ethyl-</p> <p>Pennsylvania RTK: Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester</p> <p>Florida: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester</p> <p>Minnesota: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester</p> <p>Massachusetts RTK: Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester</p> <p>New Jersey: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester</p> <p>TSCA 8(b) inventory: Benzene, dimethyl-; Benzene, methyl-; Acetic Acid, Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; N-Butyl Alcohol; Benzene, dimethyl-; Acetic Acid, Butyl Ester</p> <p>TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester</p> <p>TSCA 8(d) H and S data reporting: Benzene, ethyl-</p> <p>TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester</p>

Continued on Next Page

SARA 302/304/311/312 extremely hazardous substances: 1-Butanol; N-Butyl Alcohol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Quartz (SiO₂): Delayed (Chronic) Health Hazard; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; Solvent naphtha (petroleum), light aliph.: Fire Hazard, Immediate (Acute) Health Hazard; 1-Propanol, 2-methyl-: Fire Hazard, Immediate (Acute) Health Hazard; Acetic Acid, Butyl Ester; Isobutyl alcohol: Fire Hazard, Immediate (Acute) Health Hazard; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard
 SARA 313 toxic chemical notification and release reporting: Benzene, dimethyl- 0.122974%; Benzene, methyl- 0.108035%; 1-Butanol 0.108035%
 CERCLA: Hazardous substances.: Benzene, dimethyl-; 1-Propanol, 2-methyl-; Benzene, methyl-; Acetic Acid, Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; N-Butyl Alcohol; Isobutyl alcohol; Benzene, dimethyl-; Acetic Acid, Butyl Ester;

Other Regulations

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

WHMIS (Canada)
Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).

HCS (U.S.A.)
 Class: Flammable liquid having a flash point lower than 37.8°C (100°F).
 Class: Target organ effects.

Hazardous Material Information System (U.S.A.)	Health Hazard	* 2
	Fire Hazard	4
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	4
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Skin Contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Continued on Next Page

Preparation Information Validated by C.M. Kelly on 11/15/2002.
Verified by C.M. Kelly.
Printed 3/10/2003.

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.