

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **825-4544 RLS 758 CHEMGLAZE SPRUCE(C31963)**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 825-4544

Synonym RLS 758 CHEMGLAZE SPRUCE(C31963)

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Heavy aliphatic solvent naphtha (petroleum)	64742-96-7	50 - 70	ORAL (LD50): Acute: 5001 mg/kg [Rat]. DERMAL (LD50): Acute: 5001 mg/kg [Rabbit].	

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not applicable.

Boiling Point The lowest known value is 185°C (365°F) (Solvent naphtha (petroleum), heavy aliph.).

Melting Point Not available.

Critical Temperature Not available.

Specific Gravity Weighted average: 0.85 (Water = 1)

Vapor Pressure The highest known value is 0.07 kPa (0.5 mm Hg) (at 20°C) (Solvent naphtha (petroleum), heavy aliph.).

Vapor Density The highest known value is 5.34 (Air = 1) (Solvent naphtha (petroleum), heavy aliph.).

Volatility Not available.

Odor Threshold Not available.

Continued on Next Page

Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Not dispersible in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in methanol, diethyl ether, n-octanol, acetone. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Combustible.
Fire Hazards in Presence of Various Substances	Slightly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Special Remarks on Fire Hazards	Not available.
Flash Points	The lowest known value is Closed cup: 61.667°C (143°F). (Tagliabue.). (Solvent naphtha (petroleum), heavy aliph.)
Flammable Limits	The greatest known range is Lower: 1.1% Upper: 6% (Solvent naphtha (petroleum), heavy aliph.)
Auto-Ignition Temperature	Not available.
Products of Combustion	These products are carbon oxides (CO, CO ₂). Some metallic oxides.
Explosion Hazards in Presence of Various Substances	Slightly explosive in the presence of the following materials or conditions: open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Slightly reactive or incompatible with the following materials: oxidizing materials. Non-reactive or compatible with the following materials: reducing materials, combustible materials, organic materials, metals, acids, alkalis and moisture.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 5001 mg/kg [Rat]. (Solvent naphtha (petroleum), heavy aliph.). Acute dermal toxicity (LD50): 5001 mg/kg [Rabbit]. (Solvent naphtha (petroleum), heavy aliph.).
Effects of Acute Exposure	Hazardous in case of ingestion, of inhalation.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Solvent naphtha (petroleum), heavy aliph.]. Classified 4 (Probably not for humans.) by IARC, None. by OSHA [Carbon Black]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to kidneys, liver. Repeated or prolonged exposure to the substance can produce target organs damage.

Continued on Next Page

Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Carbon black contains trace amounts absorbed polynuclear aromatic compounds (PAH), some of which have been found to be carcinogens in animal studies. Carbon black has not been shown to cause cancer in humans or animals. (Carbon Black)
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. (1-Propanol, 2-methyl-)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Suggested protective clothing might not be adequate. Consult a specialist before handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Small Spill	Absorb with an inert material and transfer the spilled material and absorbent to an appropriate waste disposal container.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.
Storage	Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	-
Federal and State Regulations	WARNING: This product contains chemical/chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.: Benzene; Benzene, methyl-; Carbon Black WARNING: This product contains chemical/chemicals known to the state of California to cause reproductive harm (male).: Benzene WARNING: This product contains chemical/chemicals known to the state of California to cause birth defects or other reproductive harm.: Benzene; Benzene, methyl- WARNING: This product contains chemical/chemicals known to the state of California to cause cancer.: Benzene; Carbon Black Illinois toxic substances disclosure to employee act: Benzene, ethyl- New York release reporting list: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester New York acutely hazardous substances: Benzene, ethyl- Rhode Island RTK hazardous substances: Benzene, ethyl- Pennsylvania RTK: Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester Florida: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester Minnesota: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester Massachusetts RTK: Benzene, ethyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester New Jersey: Benzene, ethyl-; Benzene, methyl-; Acetic Acid, Butyl Ester; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester TSCA 8(b) inventory: Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl-; Acetic Acid,

Continued on Next Page

Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester
TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester
TSCA 8(d) H and S data reporting: Benzene, ethyl-
TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester; Acetic Acid, Butyl Ester
CERCLA: Hazardous substances.: Benzene, ethyl-: 1000 lbs. (453.6 kg); Benzene, dimethyl-:
100 lbs. (45.36 kg); 1-Propanol, 2-methyl-; Benzene, methyl-: 1000 lbs. (453.6 kg); Acetic
Acid, Butyl Ester; 1-Butanol; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester;
Isobutyl alcohol;

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications **WHMIS (Canada)** **Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).**
Class D-2A: Material causing other toxic effects (Very toxic).
HCS (U.S.A.) Target organ effects

Hazardous Material Information System (U.S.A.)	Health Hazard	* 0
	Fire Hazard	2
	Reactivity	0
	Personal Protection	G

National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	2
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact Wash with soap and water. Get medical attention if irritation develops.

Hazardous Skin Contact Not available.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Hazardous Inhalation Move the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion Do not induce vomiting. Examine the lips and mouth to ascertain if the tissues are damaged, a possible indication that toxic material was ingested. The absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Hazardous Ingestion Not available.

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information Validated by S.Bice on 2/9/2006.
Verified by S.Bice.
Printed 6/13/2006.

Continued on Next Page

SPRUCE(C31963)

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.