

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **999-017 ACID CATALYST**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 999-017

Synonym ACID CATALYST

Chemical Name Not applicable.

Chemical Family Aromatic sulfonic acid. (Acid.)

Chemical Formula Not applicable.

Material Uses Coatings: Hardener for resins.

Product Identification Number (PIN) 2924 FLAMMABLE LIQUIDS,CORROSIVE N.O.S. (ethyl acetate, toluene sulphonic acid)

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			LC ₅₀ /LD ₅₀	TLV/PEL
Ethyl alcohol	64-17-5	30-60	ORAL (LD50): Acute: 7060 mg/kg [Rat].	OSHA (Canada). TWA: 1000 ppm ACGIH (Canada). TWA: 1000 ppm
Ethyl Acetate	141-78-6	10-30	ORAL (LD50): Acute: 5600 mg/kg [Rat].	OSHA (Canada). TWA: 400 ACGIH (Canada). TWA: 400 ppm
Anhydrous para-toluenesulfonic acid	104-15-4	10-30	ORAL (LD50): Acute: 2480 mg/kg [Rat].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Acidic.

Boiling Point The lowest known value is 77°C (170.6°F) (Acetic Acid, Ethyl Ester). Weighted average: 77.98°C (172.4°F)

Melting Point May start to solidify at -83.6°C (-118.5°F) based on data for: Acetic Acid, Ethyl Ester. Weighted average: -103.58°C (-154.4°F)

Critical Temperature Not available.

Specific Gravity Weighted average: 0.89 (Water = 1)

Continued on Next Page

Vapor Pressure	The highest known value is 9.7 kPa (73 mmHg) (at 20°C) (Acetic Acid, Ethyl Ester). Weighted average: 7.08 kPa (53.1 mmHg) (at 20°C)
Vapor Density	The highest known value is 3.04 (Air = 1) (Acetic Acid, Ethyl Ester). Weighted average: 2.09 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 180 ppm (Ethanol)
Water/Oil Dist. Coeff.	The product is much more soluble in water.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersed in methanol, diethyl ether. See solubility in water, methanol, diethyl ether.
Solubility	Easily soluble in cold water, hot water, methanol, diethyl ether. Insoluble in n-octanol.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks and static discharge, of heat. Slightly flammable to flammable in presence of oxidizing materials, of reducing materials, of moisture.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Containers should be grounded. (Ethanol)
Flash Points	The lowest known value is Closed cup: -1°C (30.2°F). (Tagliabue). Open cup: -0.5°C (31.1°F). (Tagliabue). (Acetic Acid, Ethyl Ester)
Flammable Limits	The greatest known range is LOWER: 3.3% UPPER: 19% (Ethanol)
Auto-Ignition Temperature	The lowest known value is 422°C (791.6°F) (Ethanol).
Products of Combustion	These products are carbon oxides (CO, CO ₂), sulfur oxides (SO ₂ , SO ₃ ...).
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents. Slightly reactive to reactive with acids, alkalis, moisture. Non-reactive with metals.
Corrosivity	Slightly corrosive in presence of copper, of steel.
Special Remarks on Reactivity	Reacts violently with water especially when water is added to the product. (Sulfuric acid)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2480 mg/kg [Rat]. (Benzenesulfonic acid, 4-methyl-). Acute toxicity of the vapor (LC50): 8000 ppm 4 hour(s) [Rat.]. (Ethanol).
Effects of Acute Exposure	Very hazardous in case of skin contact (corrosive). Hazardous in case of ingestion. Slightly hazardous in case of eye contact (irritant), of inhalation. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.

Continued on Next Page

Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH [Ethanol]. Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [PROVEN] [Ethanol]. The substance is toxic to the reproductive system. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.
Special Remarks on Other Toxic Effects on Humans	Moderately toxic and narcotic in high concentrations. Experimentally tumorigen. (Ethanol)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Neoprene gloves. Boots.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Neoprene gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: Neutralize the residue with a dilute solution of sodium carbonate.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of sodium carbonate.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep locked up. Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	TDG CLASS 3: Flammable liquid. TDG CLASS 8: Corrosive liquid.
PIN	2 9 2 4 F L A M M A B L E PG: II LIQUIDS,CORROSIVE N.O.S. (ethyl acetate, toluene sulphonic acid)
Special Provisions for Transport	
Federal and State Regulations	New York release reporting list: Acetic Acid, Ethyl Ester Rhode Island RTK hazardous substances: Acetic Acid, Ethyl Ester Pennsylvania RTK: Ethanol; Acetic Acid, Ethyl Ester Florida: Acetic Acid, Ethyl Ester Minnesota: Ethanol; Acetic Acid, Ethyl Ester Massachusetts RTK: Ethanol; Acetic Acid, Ethyl Ester New Jersey: Ethanol; Acetic Acid, Ethyl Ester TSCA 8(b) inventory: Ethanol; Acetic Acid, Ethyl Ester; Toluenesulfonic Acid High Para TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester SARA 302/304/311/312 extremely hazardous substances: Toluenesulfonic Acid High Para

Continued on Next Page

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Acetic Acid, Ethyl Ester:
Fire Hazard, Immediate (Acute) Health Hazard

SARA 313 toxic chemical notification and release reporting: Sulfuric acid 0.13696%

CERCLA: Hazardous substances.: Acetic Acid, Ethyl Ester;

Other Regulations

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

WHMIS (Canada)
Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).
Class E: Corrosive liquid.

HCS (U.S.A.)
Class: Flammable liquid having a flash point lower than 37.8°C (100°F).
Class: Target organ effects.
Class: Corrosive material

Hazardous Material Information System (U.S.A.)

Health Hazard	* 3
Fire Hazard	3
Reactivity	1
Personal Protection	

National Fire Protection Association (U.S.A.)

Health	3
Fire Hazard	3
Reactivity	1
Specific Hazard	

Section 8. First Aid Measures

Eye Contact Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Hazardous Skin Contact Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Hazardous Inhalation Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Hazardous Ingestion Not available.

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information
Validated by C.M. Kelly on 9/18/2002.
Verified by C.M. Kelly.
Printed 9/20/2002.

Continued on Next Page

Information Contact

Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.