

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **999-036 ACCELERATOR POLYESTER**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3
Telephone (905) 885-6388 Fax (905) 885-5097
In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code 999-036
Synonym ACCELERATOR POLYESTER
Chemical Name Not applicable.
Chemical Family Synthetic polymer in organic solvent. (Paint.)
Chemical Formula Not applicable.
Material Uses Coatings: Surface coatings and finishes.
Product Identification Number (PIN) 1263 PAINT RELATED MATERIAL

Section 2. Hazardous Ingredients

Exposure limits

Name	CAS #	% by Weight	LC ₅₀ /LD ₅₀	TLV/PEL
Toluene	108-88-3	30 - 50	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	ACGIH (Canada, 1993). TWA: 50 ppm TWA: 188 mg/m ³
Ethyl Acetate	141-78-6	30 - 50	ORAL (LD50): Acute: 5600 mg/kg [Rat].	ACGIH (Canada). TWA: 400 ppm
Cobalt compounds n.o.s.		5 - 15	Not available.	Not available.
Mineral spirits	8052-41-3	5 - 15	ORAL (LD50): Acute: 5000 mg/kg [Rat]. DERMAL (LD50): Acute: 3160 mg/kg [Rabbit].	ACGIH (Canada). TWA: 525 mg/m ³ CEIL: 720 mg/m ³
Diethylene glycol monomethyl ether	111-77-3	0.1 - 1	ORAL (LD50): Acute: 7128 mg/kg [Rat]. DERMAL (LD50): Acute: 9404 mg/kg [Rabbit].	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. Odor Not available. Taste Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Not available.

Boiling Point The lowest known value is 77°C (170.6°F) (Acetic Acid, Ethyl Ester). Weighted average: 97.73°C (207.9°F)

Continued on Next Page

Melting Point	May start to solidify at -83.6°C (-118.5°F) based on data for: Acetic Acid, Ethyl Ester. Weighted average: -89.05°C (-128.3°F)
Critical Temperature	Not available.
Specific Gravity	Weighted average: 0.9 (Water = 1)
Vapor Pressure	The highest known value is 9.7 kPa (73 mm Hg) (at 20°C) (Acetic Acid, Ethyl Ester). Weighted average: 5.92 kPa (44.4 mm Hg) (at 20°C)
Vapor Density	The highest known value is 4.8 (Air = 1) (Stoddard solvent). Weighted average: 3.2 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 1 ppm (Stoddard solvent)
Water/Oil Dist. Coeff.	The product is more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Partially dispersed in methanol, diethyl ether. Very slightly dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol.
Solubility	Easily soluble in methanol, diethyl ether. Soluble in n-octanol. Partially soluble in cold water. Very slightly soluble in hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks and static discharge.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)
Flash Points	The lowest known value is Closed cup: -1°C (30.2°F). (Tagliabue). Open cup: -0.5°C (31.1°F). (Tagliabue). (Acetic Acid, Ethyl Ester)
Flammable Limits	The greatest known range is Lower: 1% Upper: 13.3% (Stoddard solvent)
Auto-Ignition Temperature	The lowest known value is 229°C (444.2°F) (Stoddard solvent).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Slightly reactive to reactive with oxidizing agents, reducing agents, organic materials, metals, acids, alkalis.
Corrosivity	Not available.
Special Remarks on Reactivity	Not available.
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 2600 mg/kg [Rat]. (Benzene, methyl-). Acute dermal toxicity (LD50): 3160 mg/kg [Rabbit]. (Stoddard solvent). Acute toxicity of the vapor (LC50): 19596 ppm 4 hour(s) [Rat]. (Acetic Acid, Ethyl Ester).
Effects of Acute Exposure	Very hazardous in case of skin contact (permeator), of ingestion, of inhalation.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH, 4 (Probably not for human.) by IARC [Acetic Acid, Ethyl Ester]. Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC [Cobalt Compounds n.o.s.]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [Ethanol, 2-(2-methoxyethoxy)-]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
Special Remarks on Other Toxic Effects on Humans	Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Splash goggles. Synthetic apron. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Impervious gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep locked up. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT RELATED PG: II MATERIAL
Special Provisions for Transport	-

Federal and State Regulations	WARNING: This product contains chemical(s) known to the State of California to cause cancer, birth defects or other reproductive harm: Benzene, methyl-	
	WARNING: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.: Benzene, methyl-	
	New York release reporting list: Acetic Acid, Ethyl Ester	
	Rhode Island RTK hazardous substances: Acetic Acid, Ethyl Ester	
	Pennsylvania RTK: Benzene, methyl-; Acetic Acid, Ethyl Ester; Ethanol, 2-(2-methoxyethoxy)-	
	Florida: Acetic Acid, Ethyl Ester	
	Minnesota: Acetic Acid, Ethyl Ester	
	Massachusetts RTK: Acetic Acid, Ethyl Ester	
	New Jersey: Benzene, methyl-; Acetic Acid, Ethyl Ester; Ethanol, 2-(2-methoxyethoxy)-	
	TSCA 8(b) inventory: Benzene, methyl-; Acetic Acid, Ethyl Ester; Ethanol, 2-(2-methoxyethoxy)-	
	TSCA 5(e) substance consent order: Acetic Acid, Ethyl Ester	
	TSCA 12(b) annual export notification: Acetic Acid, Ethyl Ester	
	SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, methyl-: Fire hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; Acetic Acid, Ethyl Ester: Fire hazard, Immediate (Acute) Health Hazard	
	CERCLA: Hazardous substances.: Benzene, methyl-: 1000 lbs. (453.6 kg); Acetic Acid, Ethyl Ester;	
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	WHMIS (Canada)	Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). Class D-2A: Material causing other toxic effects (VERY TOXIC). Class D-2B: Material causing other toxic effects (TOXIC).
	HCS (U.S.A.)	Flammable liquid Irritating material
Hazardous Material Information System (U.S.A.)	Health Hazard	2
	Fire Hazard	3
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	0
	Fire Hazard	0
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops.
Hazardous Skin Contact	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
Hazardous Inhalation	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Continued on Next Page

Section 9. Preparation Information

References -Manufacturers Material Safety Data Sheets.

Other Special Considerations Not available.

Related Information This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.

Preparation Information **Validated by Florendo Tarnate on 9/16/2005.**

Verified by Florendo Tarnate.

Printed 9/16/2005.

Information Contact Prepared by the Health, Safety and Environment Department,
Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada.
Phone: 905 885-6388
Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.