

Material Safety Data Sheet

Section 1. Product Identification and Use

Product Name - Trade Name **FW-9099 FASTWIPE DELTA**

Supplier - Manufacturer **Chemcraft International Inc.,**
155 Rose Glen Road North
P.O. Box 458
Port Hope, ON.
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code FW-9099

Synonym FASTWIPE DELTA

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			LC ₅₀ /LD ₅₀	TLV/PEL
Heavy aromatic naphtha.	64742-94-5	5-10	ORAL (LD50): Acute: 3000 mg/kg [Rat]. DERMAL (LD50): Acute: 3001 mg/kg [Rabbit].	Not available.
Light aromatic naphtha	64742-95-6	30-60	ORAL (LD50): Acute: 6960 mg/kg [Rat.].	ACGIH (Canada). TWA: 123 mg/m ³
Xylenes	1330-20-7	1-5	ORAL (LD50): Acute: 4300 mg/kg [Rat.].	ACGIH (Canada, 1992). TWA: 100 ppm STEL: 150 ppm TWA: 434 mg/m ³ STEL: 651 mg/m ³
Pseudocumene	95-63-6	10-30	Not available.	Not available.

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

Section 3. Physical Data

Physical State and Appearance Liquid.

Color Not available. **Odor** Not available. **Taste** Not available.

Molecular Weight Not applicable.

pH (1% soln/water) Neutral.

Boiling Point The lowest known value is 100°C (212°F) (Water). Weighted average: 157.22°C (315°F)

Melting Point May start to solidify at 0°C (32°F) based on data for: Water. Weighted average: -51.3°C (-60.3°F)

Critical Temperature Not available.

Specific Gravity Weighted average: 0.93 (Water = 1)

Continued on Next Page

Vapor Pressure	The highest known value is 2.3 kPa (17.2 mmHg) (at 20°C) (Water). Weighted average: 0.36 kPa (2.7 mmHg) (at 20°C)
Vapor Density	The highest known value is 4.8 (Air = 1) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 4.07 (Air = 1)
Volatility	Not available.
Odor Threshold	The lowest known value is 0.3 ppm (Benzene, dimethyl-) Weighted average: 0.63 ppm
Water/Oil Dist. Coeff.	The product is much more soluble in octanol.
Ionicity (in Water)	Not available.
Dispersion Properties	Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
Solubility	Easily soluble in diethyl ether, n-octanol, acetone. Soluble in methanol. Insoluble in cold water, hot water.

Section 4. Fire and Explosion Hazard

The Product is:	Flammable.
Fire Hazards in Presence of Various Substances	Highly flammable in presence of open flames, sparks and static discharge. Slightly flammable to flammable in presence of heat.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. (Solvent naphtha (petroleum), light arom.)
Flash Points	The lowest known value is Closed cup: 24°C (75.2°F). (Tagliabue.). Open cup: 37.8°C (100°F). (Cleveland). (Benzene, dimethyl-)
Flammable Limits	The greatest known range is LOWER: 0.6% UPPER: 7% (Solvent naphtha (petroleum), heavy arom.)
Auto-Ignition Temperature	The lowest known value is 465°C (869°F) (Solvent naphtha (petroleum), light arom.).
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Explosion Hazards in Presence of Various Substances	Highly explosive in presence of open flames, sparks and static discharge.
Special Remarks on Explosion Hazards	Not available.

Section 5. Reactivity Data

Stability	The product is stable.
Decomposition products	Not available.
Conditions of Instability	Not available.
Incompatibility with various substances	Reactive with oxidizing agents, reducing agents, organic materials, acids, alkalis. Slightly reactive to reactive with metals.
Corrosivity	Not available.
Special Remarks on Reactivity	Incompatible with peroxides. (Benzene)
Special Remarks on Corrosivity	Not available.

Section 6. Toxicological Properties

Routes of Entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3000 mg/kg [Rat]. (Solvent naphtha (petroleum), heavy arom.). Acute dermal toxicity (LD50): 3001 mg/kg [Rabbit]. (Solvent naphtha (petroleum), heavy arom.). Acute toxicity of the vapor (LC50): 6700 ppm 4 hour(s) [Rat]. (Benzene, dimethyl-).
Effects of Acute Exposure	Very hazardous in case of skin contact (irritant), of ingestion. Hazardous in case of skin contact (sensitizer), of eye contact (irritant), of inhalation.

Chronic Effects on Humans	<p>CARCINOGENIC EFFECTS: Classified 4 (Probably not for human.) by IARC, None. by OSHA [Titanium dioxide (TiO₂)]. Classified 4 (Probably not for human.) by IARC, None. by OSHA [Carbon Black].</p> <p>MUTAGENIC EFFECTS: Not available.</p> <p>TERATOGENIC EFFECTS: Not available.</p> <p>DEVELOPMENTAL TOXICITY: Not available.</p> <p>The substance is toxic to kidneys, the nervous system, liver.</p> <p>Repeated or prolonged exposure to the substance can produce target organs damage.</p>
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	<p>Prolonged or repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea and central nervous system depression.</p> <p>High level exposure to Xylene in laboratory animals, often at levels which are toxic to the mother, have affected the development of the fetus. The relevance of this to humans is not known. (Benzene, dimethyl-)</p>
Special Remarks on Other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. Narcotic in high concentrations. (Solvent naphtha (petroleum), light arom.)
Exposure Limits	Not available.

Section 7. Preventive Measures

Personal Protection	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill	Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.
Waste Disposal	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Precautions	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, acids, alkalis.
Storage	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
TDG Classification	3
PIN	1263 PAINT PG: II
Special Provisions for Transport	
Federal and State Regulations	<p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: DCC 2509; Benzene, dimethyl-; Benzene, methyl-; 1-Propanol, 2-methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: 1-Propanol, 2-methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene; 1-Propanol, 2-methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene; Benzene, methyl-</p> <p>California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: DCC 2509; Benzene; 1-Propanol, 2-methyl-</p> <p>Illinois toxic substances disclosure to employee act: Benzene, ethyl-</p> <p>New York release reporting list: Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester</p> <p>New York acutely hazardous substances: Benzene, ethyl-</p>

Continued on Next Page

Rhode Island RTK hazardous substances: Ammonia anhydrous; Benzene, ethyl-
 Pennsylvania RTK: Ammonium hydroxide ((NH4)(OH)); Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester
 Florida: Ammonia anhydrous; Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic Acid, Butyl Ester
 Minnesota: Ammonia anhydrous; Benzene, ethyl-; Acetic Acid, Butyl Ester
 Massachusetts RTK: Ammonium hydroxide ((NH4)(OH)); Benzene, ethyl-; Benzene, 1,3-dimethyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester
 New Jersey: Ammonia anhydrous; Benzene, ethyl-; Acetic acid, 2-methylpropyl ester; Acetic Acid, Butyl Ester
 New Jersey spill list: Ammonia anhydrous
 TSCA 8(b) inventory: Ammonia anhydrous; Benzene, dimethyl-; Acetic acid, 2-methylpropyl ester; 1-Butanol; Acetic Acid, Butyl Ester; Benzene, methyl-; Benzene, dimethyl-
 TSCA 5(e) substance consent order: Acetic Acid, Butyl Ester
 TSCA 8(d) H and S data reporting: Benzene, ethyl-
 TSCA 12(b) annual export notification: Acetic Acid, Butyl Ester
 SARA 302/304/311/312 extremely hazardous substances: Ammonia anhydrous; 1-Butanol
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Ammonium hydroxide ((NH4)(OH)); Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard; 1-Propanol, 2-methyl-: Fire Hazard, Immediate (Acute) Health Hazard; Benzene, dimethyl-: Fire Hazard, Immediate (Acute) Health Hazard
 SARA 313 toxic chemical notification and release reporting: Benzene, 1,2-dimethyl- 0.643116%; Benzene, dimethyl- 1.23218%
 CERCLA: Hazardous substances.: Ammonia anhydrous; Benzene, dimethyl-; Acetic acid, 2-methylpropyl ester; 1-Butanol; Acetic Acid, Butyl Ester; Benzene, methyl-; 1-Propanol, 2-methyl-;
 OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Regulations

Other Classifications

WHMIS (Canada) **Class B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).**
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).

HCS (U.S.A.) Class: Flammable liquid having a flash point lower than 37.8°C (100°F).
 Class: Irritating substance.
 Class: Target organ effects.

Hazardous Material Information System (U.S.A.)	Health Hazard	* 2
	Fire Hazard	3
	Reactivity	0
	Personal Protection	H
National Fire Protection Association (U.S.A.)	Health	2
	Fire Hazard	3
	Reactivity	0
	Specific Hazard	

Section 8. First Aid Measures

- Eye Contact** Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
- Skin Contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- Hazardous Skin Contact** Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
- Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
- Hazardous Inhalation** Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
Hazardous Ingestion	Not available.

Section 9. Preparation Information

References	-Manufacturers Material Safety Data Sheets.
Other Special Considerations	Not available.
Related Information	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
Preparation Information	Validated by C.M. Kelly on 10/11/2002. Verified by C.M. Kelly. Printed 11/22/2002.
Information Contact	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.