

# Material Safety Data Sheet

## Section 1. Product Identification and Use

Product Name - Trade Name **SS-9061 SPRAY STAIN COUNTRY OAK**

Supplier - Manufacturer **Chemcraft International Inc.,**

155 Rose Glen Road North  
P.O. Box 458  
Port Hope, ON.  
Canada L1A 3Z3

Telephone (905) 885-6388 Fax (905) 885-5097

In case of Emergency (905) 885-6388, (800) 263-7951

### For Transport Emergency or After Hours

CANUTEC (613) 996-6666

Code SS-9061

Synonym SPRAY STAIN COUNTRY OAK

Chemical Name Not applicable.

Chemical Family Synthetic polymer in organic solvent. (Paint.)

Chemical Formula Not applicable.

Material Uses Coatings: Surface coatings and finishes.

Product Identification Number (PIN) 1263 PAINT

## Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	Exposure Limits	
			LC <sub>50</sub> /LD <sub>50</sub>	TLV/PEL
Heavy aromatic naphtha.	64742-94-5	5-10	ORAL (LD50): Acute: 3000 mg/kg [Rat]. DERMAL (LD50): Acute: 3001 mg/kg [Rabbit].	Not available.
Ethylbenzene	100-41-4	10-30	ORAL (LD50): Acute: 3500 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].	TWA: 100 CEIL: 125 (ppb) TWA: 435 CEIL: 545 (ppm)
Xylenes	1330-20-7	10-30	ORAL (LD50): Acute: 4300 mg/kg [Rat]. DERMAL (LD50): Acute: >1700 mg/kg [Rabbit].	TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [Canada] TWA: 100 STEL: 150 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 100 STEL: 150 (ppm) from NIOSH [United States] TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [United States]
Light aromatic naphtha	64742-95-6	5-10	ORAL (LD50): Acute: 6960 mg/kg [Rat].	TWA: 25 (ppb) [1992] TWA: 123 (ppm) from ACGIH (TLV) [United States]
Toluene	108-88-3	30-60	ORAL (LD50): Acute: 2600 mg/kg [Rat]. DERMAL (LD50): Acute: 12210 mg/kg [Rabbit].	TWA: 200 CEIL: 300 (ppm) from OSHA (PEL) [United States] TWA: 50 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 100 STEL: 150 (ppm) from NIOSH [United States] [1997] TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [Canada]

Trace impurities and additional material names not listed above may appear in other sections of this MSDS. These materials may be listed for toxicological concerns, local compliance, or other reasons.

**Continued on Next Page**

### Section 3. Physical Data

<b>Physical State and Appearance</b>	Liquid.
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Taste</b>	Not available.
<b>Molecular Weight</b>	Not applicable.
<b>pH (1% soln/water)</b>	Neutral.
<b>Boiling Point</b>	The lowest known value is 100°C (212°F) (Water). Weighted average: 129.25°C (264.6°F)
<b>Melting Point</b>	May start to solidify at 0°C (32°F) based on data for: Water. Weighted average: -83.59°C (-118.5°F)
<b>Critical Temperature</b>	Not available.
<b>Specific Gravity</b>	Weighted average: 0.89 (Water = 1)
<b>Vapor Pressure</b>	The highest known value is 2.9 kPa (@ 20°C) (Benzene, methyl-). Weighted average: 1.73 kPa (@ 20°C)
<b>Vapor Density</b>	The highest known value is 4.8 (Air = 1) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 3.48 (Air = 1)
<b>Volatility</b>	Not available.
<b>Odor Threshold</b>	The highest known value is 2 ppm (Benzene, ethyl-) Weighted average: 1.2 ppm
<b>Water/Oil Dist. Coeff.</b>	The product is much more soluble in oil.
<b>Ionicity (in Water)</b>	Not available.
<b>Dispersion Properties</b>	Is not dispersed in cold water, hot water. See solubility in methanol, diethyl ether, n-octanol, acetone.
<b>Solubility</b>	Easily soluble in methanol, diethyl ether, n-octanol, acetone. Insoluble in cold water, hot water.

### Section 4. Fire and Explosion Hazard

<b>The Product is:</b>	Flammable.
<b>Fire Hazards in Presence of Various Substances</b>	Flammable in presence of open flames and sparks. Non-flammable in presence of shocks, of oxidizing materials, of reducing materials, of combustible materials, of organic materials, of metals, of acids, of alkalis, of moisture.
<b>Fire Fighting Media and Instructions</b>	Flammable liquid, insoluble in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
<b>Special Remarks on Fire Hazards</b>	Vapor may travel considerable distance to source of ignition and flash back. (Benzene, methyl-)
<b>Flash Points</b>	The lowest known value is CLOSED CUP: 6°C (42.8°F). (Tagliabue). OPEN CUP: 9°C (48.2°F). (Tagliabue). (Benzene, methyl-)
<b>Flammable Limits</b>	The greatest known range is LOWER: 0.6% UPPER: 7% (Solvent naphtha (petroleum), heavy arom.)
<b>Auto-Ignition Temperature</b>	The lowest known value is 432°C (809.6°F) (Benzene, ethyl-).
<b>Products of Combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ).
<b>Explosion Hazards in Presence of Various Substances</b>	Explosive in presence of open flames and sparks. Non-explosive in presence of shocks, of reducing materials, of combustible materials, of organic materials, of metals, of acids, of alkalis, of moisture.
<b>Special Remarks on Explosion Hazards</b>	Not available.

### Section 5. Reactivity Data

<b>Stability</b>	The product is stable.
<b>Decomposition products</b>	Not available.
<b>Conditions of Instability</b>	Not available.
<b>Incompatibility with various substances</b>	Reactive with oxidizing agents, reducing agents, organic materials, alkalis. Slightly reactive to reactive with metals, acids. Non-reactive with combustible materials, moisture.

Continued on Next Page

<b>Corrosivity</b>	Non-corrosive in presence of glass, of aluminum, of zinc, of copper, of stainless steel(304), of stainless steel(316).
<b>Special Remarks on Reactivity</b>	Not available.
<b>Special Remarks on Corrosivity</b>	Not available.

## Section 6. Toxicological Properties

<b>Routes of Entry</b>	Dermal contact. Eye contact. Inhalation. Ingestion.
<b>Toxicity to Animals</b>	Acute oral toxicity (LD50): 2600 mg/kg [Rat.]. (Benzene, methyl-). Acute dermal toxicity (LD50): >1700 mg/kg [Rabbit]. (Benzene, dimethyl-).
<b>Effects of Acute Exposure</b>	Very hazardous in case of skin contact (irritant, permeator). Hazardous in case of skin contact (sensitizer), of eye contact (irritant), of ingestion, of inhalation (lung irritant). Non-corrosive for skin.
<b>Chronic Effects on Humans</b>	<b>CARCINOGENIC EFFECTS:</b> Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC, D (Not classifiable for human or animal.) by EPA [Benzene, dimethyl-]. Classified 4 (No evidence.) by NTP [Benzene, methyl-]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC, D (Not classifiable for human or animal.) by EPA [Benzene, methyl-]. <b>MUTAGENIC EFFECTS:</b> Not available. <b>TERATOGENIC EFFECTS:</b> Not available. <b>DEVELOPMENTAL TOXICITY:</b> Not available. The substance is toxic to kidneys, the nervous system, liver, upper respiratory tract, skin, eyes, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.
<b>Special Remarks on Toxicity to Animals</b>	Not available.
<b>Special Remarks on Chronic Effects on Humans</b>	Inhalation of vapors may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation. (Benzene, methyl-)
<b>Special Remarks on Other Toxic Effects on Humans</b>	Exposure can cause lung irritation, chest pain and oedema which may be fatal. (Benzene, methyl-)
<b>Exposure Limits</b>	<b>Benzene, ethyl-</b> TWA: 100 CEIL: 125 (ppb) TWA: 435 CEIL: 545 (ppm) <b>Benzene, dimethyl-</b> TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [Canada] TWA: 100 STEL: 150 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 100 STEL: 150 (ppm) from NIOSH [United States] TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [United States] <b>Solvent naphtha (petroleum), light arom.</b> TWA: 25 (ppb) [1992] TWA: 123 (ppm) from ACGIH (TLV) [United States] <b>Benzene, methyl-</b> TWA: 200 CEIL: 300 (ppm) from OSHA (PEL) [United States] TWA: 50 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 100 STEL: 150 (ppm) from NIOSH [United States] [1997] TWA: 100 STEL: 150 (ppm) from OSHA (PEL) [Canada]
	Consult local authorities for acceptable exposure limits.

## Section 7. Preventive Measures

<b>Personal Protection</b>	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
<b>Personal Protection in Case of a Large Spill</b>	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
<b>Engineering Controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
<b>Small Spill</b>	Absorb with an inert material and put the spilled material in an appropriate waste disposal.

<b>Large Spill</b>	Toxic flammable liquid, insoluble or very slightly soluble in water. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.	
<b>Waste Disposal</b>	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
<b>Precautions</b>	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, organic materials, alkalis.	
<b>Storage</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).	
<b>TDG Classification</b>	Class 3: Flammable liquid.	
<b>PIN</b>	1263 PAINT	<b>PG: II</b>
<b>Special Provisions for Transport</b>	Not available.	
<b>Federal and State Regulations</b>	California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl- New York release reporting list: Benzene, dimethyl- Rhode Island RTK hazardous substances: Ammonia, anhydrous; Benzene, dimethyl-; Benzene, methyl- Pennsylvania RTK: Ammonia, anhydrous: (environmental hazard); Benzene, dimethyl-: (environmental hazard); Benzene, methyl-: (environmental hazard) Florida: Ammonia, anhydrous; Benzene, dimethyl-; Benzene, methyl- Minnesota: Ammonia, anhydrous; Benzene, dimethyl-; Benzene, methyl- Michigan critical material: Benzene, dimethyl-; Benzene, methyl- Massachusetts RTK: Ammonia, anhydrous; Benzene, dimethyl-; Benzene, methyl- New Jersey: Ammonia, anhydrous; Benzene, dimethyl-; Benzene, methyl- New Jersey spill list: Ammonia, anhydrous TSCA 8(b) inventory: Ammonia, anhydrous; Benzene, ethyl-; Benzene, dimethyl-; Benzene, methyl- TSCA 8(d) H and S data reporting: Benzene, methyl- SARA 302/304/311/312 extremely hazardous substances: Ammonia, anhydrous SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Benzene, ethyl-: fire, immediate health hazard; Benzene, dimethyl-: fire, immediate health hazard SARA 313 toxic chemical notification and release reporting: Benzene, ethyl- 11.0259%; Benzene, dimethyl- 25.7272%; Benzene, methyl- 35.81% CERCLA: Hazardous substances.: Ammonia, anhydrous; Benzene, dimethyl-: 100 lbs. (45.36 kg); Benzene, methyl-: 1000 lbs. (453.6 kg);	
<b>Other Regulations</b>	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).	
<b>Other Classifications</b>	<b>WHMIS (Canada)</b>	<b>CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).</b> <b>CLASS D-2A: Material causing other toxic effects (VERY TOXIC).</b> <b>CLASS D-2B: Material causing other toxic effects (TOXIC).</b>
	<b>HCS (U.S.A.)</b>	Class: Flammable liquid having a flash point lower than 37.8°C (100°F). Class: Irritating substance. Class: Target organ effects.
<b>Hazardous Material Information System (U.S.A.)</b>	<b>Health Hazard</b>	* 2
	<b>Fire Hazard</b>	3
	<b>Reactivity</b>	0
	<b>Personal Protection</b>	h
<b>National Fire Protection Association (U.S.A.)</b>	<b>Health</b>	2
	<b>Fire Hazard</b>	3
	<b>Reactivity</b>	0
	<b>Specific Hazard</b>	

## Section 8. First Aid Measures

<b>Eye Contact</b>	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
<b>Hazardous Skin Contact</b>	Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Hazardous Inhalation</b>	Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.
<b>Hazardous Ingestion</b>	Not available.

## Section 9. Preparation Information

<b>References</b>	-Manufacturers Material Safety Data Sheets.
<b>Other Special Considerations</b>	Not available.
<b>Related Information</b>	This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by CPR.
<b>Preparation Information</b>	<b>Validated by A. McLeod on 10/27/2000.</b> <b>Verified by A. McLeod.</b> <b>Printed 9/18/2002.</b>
<b>Information Contact</b>	Prepared by the Health, Safety and Environment Department, Chemcraft International Inc., P.O. Box 458, 155, Rose Glen Road North, Port Hope, ON. Canada. Phone: 905 885-6388 Fax: 905 885-5097

### Notice to Reader

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*