

Standard Product Configuration Table: Random Orbital Sander - 12,000 RPM

All Central Vacuum machines use 3/4 in. Vacuum Hose Fittings Standard. 1 in. is available for Central Vacuum. All Self Generated Vacuum machines use 1 in. Vacuum Hose Fittings Standard. 3/4 in is available for Self Central Vacuum. All 3" machines are shrouded with 1/4-20 male pad attachment.

Orbit	Pad Face	Vac Type	Pad Type	Pad P/N	Model No
3/32 in.(2.5mm)	Vinyl	Non-Vac	3"(77 mm) diameter for PSA discs	1232100	030200
3/32 in.(2.5mm)	Vinyl	Central Vac	3"(77 mm) diameter for PSA discs	1232110	030234
3/32 in.(2.5mm)	Vinyl	Self-Gen Vac	3"(77 mm) diameter for loop discs	1232110	030267
3/32 in (2.5mm)	Hook	Non-Vac	3"(77 mm) diameter for PSA discs	1232102	030201
3/32 in (2.5mm)	Hook	Central Vac	3"(77 mm) diameter for PSA discs	1232112	030235
3/32 in (2.5mm)	Hook	Self-Gen Vac	3"(77 mm) diameter for loop discs	1232112	030268

Specification for 3 in. (77mm) Light Weight Random Orbital Sanders

Model Number	Motor hp W		Pad Dim		*AIR Flow		Product Net Wt.		Height		Length	
			Inch (mm)	mm	SCFM (LPM)		lb. (kg)		Inch (mm)	Inch (mm)		
030300	0.28	209	3	77	17	481	1.5	0.68	3.5	88	5.0	126
030334	0.28	209	3	77	17	481	1.7	0.78	3.5	88	7.4	187
030367	0.28	209	3	77	17	481	1.8	0.80	3.5	88	7.7	196

Additional Specifications: Air Inlet Thread is 1/4" NPT and Hose I.D. is 1/4" (6mm). *Air flow/consumption specification are @ 90 psig (6.2 bar)